

5. Estimation for Primary Tunnel Lining Loads

University of Alberta, 김학준 박사 / 대전대학교 지질공학과 교수

University of Alberta

Estimation for Primary Tunnel Lining Loads

by

Hak Joon Kim

A thesis submitted to the Faculty of Graduate Studies and Research in partial fulfillment of the requirements for the degree of Doctor of Philosophy

in

Geotechnical Engineering

Department of Civil and Environmental Engineering

Edmonton, Alberta

Fall 1997

Current Address:
Department of Geological Engineering
College of Engineering
The University of Tajon
96-3 Yongun-Dong
Tong-gu, Taejon
300-716

ABSTRACT

Prediction of lining loads due to tunnelling is one of the major issues to be addressed in the design of a tunnel. The objective of this study is to investigate rational and realistic design loads on tunnel linings. Factors influencing the lining load are summarized and discussed. The instruments for measuring the lining loads are reviewed and discussed because field measurements are often necessary to verify the design methods.

Tunnel construction in the City of Edmonton has been very active for storm and sanitary purposes. Since the early 1970's, the city has also been developing an underground Light Rail Transit system. The load measurements obtained from these tunnels are compared with the results from the existing design methods. However, none of the existing methods are totally satisfactory. Therefore, there is some room for improvement in the prediction of lining loads.

The convergence-confinement method is reviewed and applied to a case history of a tunnel in Edmonton. The convergence curves are obtained from 2-D finite element analyses using three different material models and theoretical equations. The limitation of the convergence-confinement method is discussed by comparing these curves with the field measurements. Three-dimensional finite element analyses are performed to gain a better understanding of stress and displacement behaviour near the tunnel face.

An improved design method is proposed based on the review of existing design methods and the performance of numerical analyses. A specific method or combination of two different methods is suggested for the estimation of lining loads for different conditions of tunnelling. A method to determine the stress reduction factor is described. Typical values of dimensionless load factors nD/H for tunnels in Edmonton are obtained from parametric analyses. Finally, the loads calculated using the proposed method are compared with field measurements collected from various tunnels in terms of soil types and construction methods to verify the method. The proposed method gives a reasonable approximation of the lining loads.

The proposed method is recommended as an approximate guideline for the design of tunnels, but the results should be confirmed by field measurements due to the uncertainties of the ground and lining properties and the construction procedures.

This is the reason that in-situ monitoring should be an integral part of the design procedure.

1. Introduction

1.1 General

Prediction of lining loads due to tunnelling is one of the major issues to be addressed in the design of a tunnel. However, the problem is not easily solved due to uncertainties and variations of the ground conditions, the redistribution of the in-situ stresses related to the ground deformation before and after lining installation, and the differences in construction procedures. Therefore, most tunnels are often built too conservatively, i.e., more support is used than is necessary.

It is a well-known fact that tunnel lining seldom carries the full total load of the soil or rock located above the tunnel crown. In practice, various lining thicknesses have been used for similar ground conditions. It has been recognized that such variations reflect the absence of consistent design principles. The objective of this study is to investigate rational and realistic design loads on tunnel linings.

1.2 Scope and Organization of the Thesis

There are many existing lining design methods available. The response of the ground and support during excavation should be fully understood to review the problem of the existing design methods. Two or three dimensional finite element analyses can be used for this purpose.

An improved design method is proposed based on the review of the existing design methods. The best way to evaluate the validity of the method is to compare the calculated loads with the field measurements. Therefore, loads calculated using the proposed method are compared with field measurements from the case histories collected from many different areas to verify the method.

Chapter 2 presents discussions on the soil response to tunnelling, factors influencing the load on the liner, and available design methods to estimate the lining loads. It is very important to understand factors influencing the lining load to predict the load reliably. The existing design methods are classified based on the calculation

procedure on which a particular method is developed. The validity of the design methods is discussed briefly based on literature reviews.

Field measurements are often necessary to verify the design methods or assumptions and improve models of ground behaviour. Therefore, the instruments for measuring the lining loads are reviewed in Chapter 3. The methods for the processing of measurements are also presented for two different lining systems. Finally, certain instruments are recommended for the measurement of lining loads for specific conditions.

The validity of the existing design methods is reviewed in Chapter 4 by comparing the loads calculated using the methods with the field measurements obtained from several tunnels in Edmonton. Conclusions concerning the existing design methods are presented based on the comparison. The use of correction factors for the existing design methods is also discussed in this chapter.

The design of a tunnel liner is a ground and structural problem. Ground-support interaction is a consequence of the resistance with which the liner reacts against the movement of the surrounding ground into the excavated opening. The convergence-confinement method (CCM) is one approach to the analysis of ground-support interaction. In Chapter 5, the convergence-confinement method is reviewed and applied for a case history of a tunnel in Edmonton. The convergence curves are obtained from two-dimensional finite element analyses using three different material models and theoretical equations. The limitation of the CCM is also discussed by comparing these curves with the actual field measurements obtained from a tunnel in Edmonton.

Three-dimensional finite element analyses are performed in Chapter 6 in order to have a better understanding of stress and displacement behaviour near the tunnel face. The influence of the construction sequences in ground-support interaction is investigated using the 3-D analyses. The possible causes of the differences in the final equilibrium stresses and displacements on the liner between the 2-D and 3-D analyses are presented. The difficulties involved in the 3-D analyses are also discussed in this chapter.

An improved design method is proposed in Chapter 7 based on the review of the existing design methods and numerical analyses. A method to determine the stress

reduction factors is described in detail. In addition, a specific method or combination of two different methods is suggested to use for each type of tunnelling for the estimation of lining loads. Finally, the results from the proposed method are compared with field measurements of the case histories collected from many different areas to verify the method.

Chapter 8 presents a brief summary of this research and the main conclusions.

Since my original Ph.D thesis is composed of more than 300 pages, it is impossible to include all of the contents in this paper. Therefore, I will summarize it as much as I can to show you what I did for my Ph.D study.

2. Methods for Predicting Lining Loads

The lining is designed to support the weight of the overburden and a horizontal pressure equal to some fraction of it. The primary lining is usually designed to resist all transient loads developed during construction activities as well as the short-term ground loads. The secondary lining is used to ensure a safe support of the tunnel for the any other additional loading resulting from future changes in the overall physical conditions and the possible increased long-term ground loads.

However, tunnel linings seldom carry the full total load of the overburden. The soil above the tunnel is only partly supported by the liner. What occurs in all tunnels is that in-situ stresses are redistributed around the opening due to the inherent shear strength and continuity of the ground. This transfer of pressure from a yielding mass of soil onto adjoining stationary parts is called the arching effect. The lining theoretically has to support only those stresses not arched to the adjacent ground.

The prediction of lining loads for the lining design has always been the goal of tunnel engineers. However, problems exist because of the uncertainties and variations in the ground conditions, the redistribution of the in-situ ground stresses related to the ground deformations before and after lining installation, and construction procedures such as the length of the period during which the excavation is left unsupported. This chapter presents discussions on the soil response to tunnelling, factors influencing the load on the liner and available design methods to estimate the lining loads.

There are several basic requirements of a good design method. First, the design method should be simple to use. Duddeck and Erdmann (1985) reviewed the progress

of the development of design models. They concluded that the available design methods are simple enough for practical applications. In other words, if a design method is very complex or time consuming to apply, the method will not be widely used by practical engineers. Second, the design method should consider the stress release occurring before the installation of a liner in some way. Third, the method should take into account the plastic behaviour of the ground as well as that of elastic ground.

The instruments for measuring the lining loads are reviewed and discussed in the following chapter because field measurements are often necessary to verify the design methods. The validity of the existing design methods is reviewed in Chapter 4 by comparing the results from the methods with the field measurements obtained from several tunnels in Edmonton.

3. Tunnel Load Measurements

Prediction of lining loads due to tunnelling is one of the major issues to be addressed in the design of a tunnel. The existing design methods do not consider some of the details of construction and the variation of geology along the tunnel section in longitudinal and vertical directions. Therefore, field measurements are often necessary to verify the design methods or assumptions and improve models of ground behaviour. The results can be used in the design of upcoming tunnel sections for the same tunnel project or for future tunnels working in similar material with the similar construction methods.

The lining stress or load can be measured directly or indirectly using pressure cells, flat jack tests, lagging deflection, rod extensometers, strain gauges, or load cells. The magnitude and distribution of stresses acting on the lining can be obtained from the measurement. In this chapter, the instruments for measuring the lining load are reviewed and discussed in detail.

Pressure cells are not generally recommended for measuring lining loads because of the long and unsuccessful history of attempting to do so. Flat jack tests can be an economical and fast procedure to evaluate the stresses in concrete linings. However, more case histories should be collected to improve the accuracy of the method. Lagging deflection can be used for estimating lining loads in a rib and lagging

support system. Again, the method should be applied with caution because the amount of lagging deflection varies depending on several factors as explained in Section 3.2.3. The use of rod or tape extensometers for estimating lining loads requires several assumptions, which make the method only an approximate solution.

It was shown that strain gauges and load cells are the most effective and reliable ways for measuring lining loads. If measurements from both strain gauges and load cells are obtained in combined lining systems, the lining loads shared between two different lining types should be considered when calculating an average lining load. The pattern of strain throughout the lining may be highly variable and difficult to convert into stress without certain assumptions of the stress distribution. Therefore, a large number of strain gauges are generally required to examine the overall behaviour of the lining because a strain gauge provides reliable measurement of strain at only one point in the lining. On the other hand, one or two load cells provide an overall average measurement of normal loads in the lining. Therefore, using load cells is more cost effective than using strain gauges. However, the assumption of stress distribution around a tunnel should be well approximated to calculate reliably the average radial stresses acting on the lining.

The loads due to other than earth pressure may affect the measurements of lining loads. Special care should be taken for the measurements of strain gauges in the ribs and precast concrete segmented linings because stresses due to the installation procedure such as outward expansion of the linings by the radially directed rams may affect the readings. Measurements from load cells are not much affected by the expansion of the linings because the load cells are generally activated after the pressure in the expansion jacks is released. The forces resulting from the longitudinal reaction of the mole may be significant for the measurements of lining loads. In order to isolate the effects of the loads from the mole, differential strains can be used rather than absolute strains. In concrete linings, high lining strains may develop locally as a result of creep, shrinkage, and temperature changes. Therefore, strain measurements in concrete linings should be corrected to consider these factors.

Long-term load measurements in a tunnel are important to check the stability of a tunnel because lining loads generally increase as time passes. Therefore, considering the high humidity and dirt conditions in a tunnel, the vibrating wire strain

gauges or load cells are recommended for the load measurements in a tunnel. The geology and construction sequence, including the location of the tunnel face with respect to the instrumented lining, should be recorded in detail because they are closely related to the variation of the lining load. Several ribs in a row, usually three or four consecutive ones, should be instrumented to allow for variation in the load due to variations in geology and support installation details. In the following chapter, measured lining loads from case histories are presented and compared with the lining loads from existing theories.

4. Comparison of Lining Loads from Measurements and Existing Design Methods

4.1 Introduction

Methods for predicting and measuring lining loads were reviewed in the previous two chapters. Many factors contribute to the differences in the lining loads of many different tunnels as explained before. The validity of the existing design methods, three from ring and plate models and one from numerically derived methods, is reviewed in this chapter by comparing the loads calculated using the methods with the field measurements obtained from several tunnels in Edmonton. The use of correction factors for the existing design methods is also discussed in this chapter.

4.2 Comparison of Field Measurements with the Existing Theories

Soil pressures on tunnel linings can be expressed either in terms of the percentage of overburden pressure or in the form of:

$$P=n\gamma D$$

where

P= the applied pressure

n= a dimensionless factor

γ = unit weight of soil

D= tunnel diameter.

A summary of the loads carried by the primary support system on Edmonton tunnels is shown in Table 1. Four different design methods, those of Peck et al., Muir Wood, Einstein and Schwartz, and Eisenstein and Negro, were compared with the actual load

measurements in this study. In all applications of the methods, no attempts were made to best fit the observed lining performances.

The measured and calculated dimensionless factors (n) for the primary lining in Edmonton tunnels are shown in Figure 1.

4.3 Conclusions versus Existing Design Methods

Lining loads calculated using four different design methods were compared with actual load measurements in the previous section. Peck's method consistently gave much higher lining loads than those from measurements as expected. Peck's method was calculated based on the assumption of an overpressure loading condition, which implies that the tunnel opening has been excavated and supported even before the full overburden pressure is applied. As a result, Peck's method consistently overestimates the lining loads.

Einstein and Schwartz's method also generally overestimated the lining loads even though the method gave a better approximation than Peck's method. Their method assumes an excavation unloading condition, which indicates that the tunnel opening is excavated and supported after the full overburden pressure is applied. Therefore, stress redistribution induced by the opening was considered in their method. However, the opening is simultaneously excavated and supported in one step without consideration of the stress reduction occurring prior to lining installation.

Muir Wood suggested taking only 50 % of the overburden pressure, taking into consideration some stress reduction of the ground around a tunnel opening before the lining was placed. Muir Wood's method gave a better approximation than the previous two methods, with an average of 37 % overestimation of the lining load. Actually, the stress reduction factor of 50 % worked reasonably well for soils in Edmonton but can be misleading for certain geologic materials.

The common problems with the above three methods are that they make assumptions about only concerning linear elastic ground, and there is uncertainty about the determination of the stress reduction factor. Eisenstein and Negro's method not only considered non-linear ground behaviour but also was capable of calculating the stress reduction factor. Therefore, the method gave the closest estimates of the

actual lining loads. In conclusion, Eisenstein and Negro's method gave the closest estimates of the actual lining loads.

4.4 Application of Stress Reduction Factors to the Existing Design Methods

Eisenstein and Negro (1985) suggested that the stress reduction factor found using their method could be used coupled with any analytical solution for calculation of thrust forces and bending moments. For example, Muir Wood presented a closed form solution, recommending a 50 % reduction of the full overburden pressures to account for face and heading effects occurring prior to lining installation. The 50 % stress reduction is an arbitrary value, and various suggestions have been given by others, e.g. about a 33 % stress reduction as suggested by Panet (1973). Einstein and Schwartz (1980) also suggested that the stress reduction factor could be between 15 % and 100 % according to simple analytical and numerical techniques and case study data.

Instead of applying this rather arbitrary reduction, the reduced unit weight of soil found from Eisenstein and Negro's method was used for each tunnel to reevaluate the lining load from the analytical methods. The results are shown in Figure 2. The results encourage the use of the reduced unit weight considering that the stress release occurred before lining installation. The use of stress reduction factors, coupled with other analytical solutions, for the prediction of lining loads is further discussed in detail in Chapter 7.

In conclusion, none of the above methods are totally satisfactory for the estimation of lining loads even though certain methods can give reasonable results under specific conditions. Therefore, there is some room for improvement in the prediction of lining loads. An improved design method will be proposed in Chapter 7 based on the review of existing design methods in this chapter and performance of numerical analyses in the following two chapters.

5. Ground- Support Interaction During Excavation

5.1 Introduction

Tunnel excavation changes the state of stress and stiffness around the opening. The installation of a support system, which interacts with the soil, further alters the

stress and stiffness of the ground. Ground-support interaction is a consequence of the resistance with which the liner reacts against the movement of the surrounding ground into the excavated opening. Kuesel (1987) stated that the design of a tunnel liner was not a structural problem but a ground and structural problem, with the emphasis on the ground because the loads acting on a liner are not well defined and its behaviour is controlled by the properties of the surrounding ground.

The transfer of loads from the excavated ground to the tunnel liner depends on the stress-strain-time properties of the ground, the relative stiffness between the liner and the ground, the initial stresses existing in the ground, the method of excavation, type and manner of placement of the liner and the distance between the tunnel face and the point of liner activation. The convergence-confinement method has played a major role in understanding the ground-liner interaction in advancing tunnels. In this chapter, the convergence-confinement method is reviewed and applied for a case history of a tunnel in Edmonton. The convergence curves are obtained from two-dimensional finite element analyses using three different material models and theoretical equations. These curves are compared with actual field measurements.

5.2 Analysis of Experimental Tunnel

An Experimental tunnel was chosen for the present analyses because of the availability of considerable field measurements of tunnel performance as well as soil parameters. The tunnel is described in detail in Sec. 4.2.6. SIGMA/W was used for the two dimensional finite element analysis. SIGMA/W, developed by GEO-SLOPE International Ltd, is a finite element program that can be used to conduct two-dimensional or axisymmetric stress and deformation analyses of earth structures.

The finite element meshes used for the analyses are shown in Figure 3. Initial in-situ stress before excavation was applied to the section assuming 21 KPa of unit weight and a uniform in-situ stress ratio. The deformations and strains from the first step have no relevance and are considered to be zero. Two-dimensional load-deformation analyses were performed through excavation of a tunnel section using three different material models: linear-elastic, hyperbolic and elastic-plastic.

The elements in the tunnel section were deactivated in one step to simulate the excavation. The internal forces, which are equal to in-situ stresses but opposite

direction, were applied to the nodes along the excavated tunnel boundary to prevent any soil movement due to excavation. The procedure to calculate the equivalent internal forces for initial stresses is shown in Figure 4. The upper diagram shows the contributing areas for planar two-dimensional elements with width equal to 1 unit. The forces, F_x and F_y , were reduced to zero in 11 different steps with a 10 % deduction of forces for each step.

5.3 Summary and Conclusions

The convergence-confinement method is one approach to the analysis of ground-support interaction. The method was reviewed in detail in this chapter. The CCM has a great advantage in explaining the phenomena governing the ground-liner interaction. However, the method may not be appropriate as a direct design tool except for special cases such as deep tunnels and highly pressurized ground due to the limitations mentioned in Sec. 5.2.2. To have a better understanding of the method, especially the effect of a material model on the convergence curve, two-dimensional finite element analyses were performed.

The procedures to simulate the excavation for two-dimensional analyses were presented in Sec. 5.3.2. The convergence curves were obtained from two-dimensional finite element analyses using three different material models and theoretical equations. The limitation of the use of 2-D finite element methods combined with CCM for the estimation of the final load and displacement around a tunnel was discussed by comparing these curves with the actual field measurements obtained from a tunnel in Edmonton.

Most tunnels clearly show three-dimensional behaviour within the region bounded by one to two diameters ahead of the face to one diameter behind the location of liner activation. The ground displacements occurring ahead of the face could not be considered in the two-dimensional finite element analyses. In addition, two-dimensional analyses can not model the fact that as the tunnel advances, the excavation is done in a zone ahead of the face in which the stress condition has already been changed by the approach of the face.

To gain a better understanding of stress and displacement behaviour near the tunnel face, three-dimensional finite element analyses are performed in the following chapter.

6. Three Dimensional Response of Ground

6.1 Introduction

The plane strain finite element analysis is still widely used for tunnel designs because of its simplicity and low cost compared to three-dimensional finite element analyses. However, in the vicinity of the advancing face, the longitudinal displacements are not zero.

Eisenstein and Branco (1985) observed the longitudinal movement of the ground ahead of the advancing face towards the face using inclinometers. The soil moved back to its original position after the TBM passed by the points that initially moved towards the face. Therefore, the final differential longitudinal displacements from the field measurements were small close to a two dimensional plane strain condition. However, as Branco (1981) pointed out, the response of strain path dependent soil would not be completely described in a two dimensional plane strain representation because the strains were not zero during the tunnel advance.

In addition, as mentioned in the previous chapter, the plane strain analyses have difficulty determining the relationship between the position of liner installation and the amount of ground displacement occurring before installation of the liner. Furthermore, two dimensional analyses cannot model the fact that as the tunnel advances, the excavation is done in a zone ahead of the face in which the stress condition has already been changed by the approach of the face. Therefore, in order to gain a better understanding of stress and displacement behaviour near the tunnel face, three-dimensional finite element analyses were performed and presented in this chapter.

6.2 Three-Dimensional Finite Element Analyses

In order to understand the behaviour of stress and displacement near the tunnel face, three-dimensional finite element analyses were performed using the program SAGE developed by Chan (1985) at the University of Alberta. The Experimental

tunnel was chosen for the present analyses because of the availability of considerable field measurements of tunnel performance as well as soil parameters. The tunnel was bored through till and had an excavated diameter of 2.56 m. Each metre of the precast concrete lining consists of four segments with 0.11 m thickness.

The same cross section as for the 2-D analyses was used for the transversal section of the 3-D mesh in order to compare the results between them. The longitudinal cross section of the 3-D mesh is shown in Figure 5. A total of 10 slices with 1220 finite elements and 5101 nodal points were used for the analyses. The final mesh was finer than most of three-dimension meshes found in the literature.

6.3 Convergence Curves

The concept of convergence-confinement method was explained in detail in the previous chapter. However, the previous convergence curves do not include the actual load transfer mechanisms existing at the tunnel face.

The ground reaction curves or convergence curves are drawn for slices 5 and 6 by combining radial stresses and displacements obtained in the middle section of each element. The displacements are obtained for nodes at the excavation line. The stresses for the crown, springline and floor are obtained from the points located about 2 cm, 1.5 cm and 1 cm respectively from the excavated boundary, which are close enough from the nodal points used to get the displacements.

Figure 6 showed the convergence curves of the springline for slices 5 and 6 without the installation of the liner. The radial stresses are normalized to the in-situ stress. The convergence curves for slices 5 and 6 showed similar trends. The displacements started to occur ahead of the face with a slight increase of radial stresses from the in-situ stress due to the arching effect along the longitudinal direction of the tunnel. The dimensionless radial stresses decreased to about 0.91 when the face advanced 0.325 m behind the reference point A. The radial stresses dropped close to zero at point B after the face passed the points. The radial stresses of unsupported section between points B and C did not drop to zero because the stresses were obtained about 1.5 cm inside of the excavated boundary and the mesh was not fine enough to get zero stress in the boundary. The convergence curves between points B and C did not coincide because the excavation round length after the passage of

reference points of slices 5 and 6 were slightly different. However, the final stresses and displacements for those two points were exactly the same when the face advanced far away from those points as shown at point C.

Figure 7 presents the convergence curves obtained from two-dimensional linear elastic analyses with the results of 3-D analyses for slice 5 without liner. The final equilibrium points are almost the same for the both analyses but the ground responses are completely different. The conventional plane strain convergence curve could not consider the 3-D arching effect occurring ahead of the face and the fast stress reduction in the unsupported section.

The convergence curves of slice 5 with the installation of the liner are shown in Figure 8. The curves clearly show the influence of lining installation on the stress and displacement distributions at the crown, springline, and floor. There were increases of radial stresses without much displacement as the tunnel face advances further after the liner was installed at slice 5 in step 9. The stresses and displacements at those points were finally stabilized when the tunnel face advanced about 2 diameters away from the points. The final loads and displacements on the lining depend on the relative stiffness of the lining and the ground and the length of unsupported section at the time of lining installation.

6.4 Summary and Conclusions

In this chapter, 3-D finite element analyses have been reviewed and performed to gain a better understanding of stress and displacement behaviour near the tunnel face. The radial displacements and the radial stresses of the ground have been obtained from the 3-D analyses with and without the liner. The results were summarized in the previous sections. The stress distribution along the tunnel clearly showed the influence of the construction sequences in ground-support interaction. The stresses on the liner may vary because of the length of the lining and the distance between the lining and the tunnel face even though all the other material properties of the ground and the liner, the tunnel geometry and the in-situ stresses are the same.

The convergence curves were obtained by combining the radial stresses and the displacements. The final radial stresses from the 2-D analyses with the confinement curve and from the 3-D analyses did not coincide probably because the convergence

curve of 2-D was obtained from the analysis without the liner installation. The difference was larger as the distance of the unsupported section was reduced in the sequence of tunnel construction. Therefore, the convergence-confinement method should be used carefully when the excavation has a shorter length of unsupported section throughout the construction.

The responses of the ground around an advancing tunnel certainly show three-dimensional nature and cannot be considered properly by a two-dimensional model. However, 3-D analysis is not an easy task to perform because of the difficulties involved in the preparation of the input data and the handling of the output data. This is one of the reason that a simple design method should be available considering the three-dimensional nature of the ground around an advancing tunnel. In the following chapter, an improved design method is proposed to have better approximation for the behaviour of the tunnel without applying complex analyses.

7. Validation and Recommendations

7.1 Introduction

The validity of the existing design methods was reviewed in Chapter 4 by comparing the loads calculated using the methods with the field measurements obtained from several tunnels in Edmonton and other areas. However, none of the existing methods were totally satisfactory for the estimation of lining loads because they could not consider all the factors affecting lining loads. Because certain methods could give reasonable results under specific conditions, an improved design method is proposed in this chapter using the existing design methods.

A design method for the prediction of lining loads should include the decrease of lining loads due to the stress release before lining installation as explained in the previous two chapters. The use of stress reduction factors, coupled with other analytical solutions, for the prediction of lining loads was discussed briefly in Sec. 4.7. The results encouraged the use of the reduced unit weight considering that the stress release occurred before lining installation. Therefore, a method to determine the stress reduction factors is described in detail in this chapter. In addition, a specific method or combination of two different methods is suggested for each type of tunnelling for the estimation of lining loads. Finally, the proposed method is compared with field

measurements from the case histories collected from many different areas to verify the method.

7.2 Estimates of Stress Reduction Factors

Stress reduction factors can be found combining the radial displacements and a full range of normalized convergence curves in a variety of geometric and geotechnical conditions, as presented by Negro (1988). However, obtaining stress reduction factors using the table and diagrams can be tedious and time consuming even though it is not difficult. Therefore, using the table and diagrams, final three tables, which were not presented in this paper, were obtained for the stress reduction factors (α) as a function of the support delay length X for three different in-situ stress ratios by the current author.

The tables clearly show several characteristics of stress reduction factors. First, stress reduction factors (α) do not increase much from an X/D of 1 to an X/D of 2 even though more stress is released as X/D increases. As a result, the stress reduction factors obtained for an X/D of 1 can be used for an X/D of greater than 1 without much error. Second, the stress reduction factors also were not sensitive to the values of Z/D , especially with a Z/D between 3 and 6, even though slightly more stress was released as Z/D increases. Therefore, the stress reduction factors for a Z/D of 3 can be used for a Z/D of 6.

As a result, Table 2 is suggested for the estimates of the stress reduction factors instead of the three tables for its simplicity. According to the study of case histories collected in places other than Edmonton, the table may be used for a Z/D of up to 9 or more. The study of case histories also showed that the in-situ stress ratio of unity could be used for tunnels having a ratio greater than 1.

Calculation of equivalent friction angles is needed for soils with a non-zero cohesive strength component and with failure ratios different from unity using the following equations:

$$\phi_a = \arcsin\left[\frac{1 + \left(\frac{\sigma_3}{c}\right) \tan \phi}{1 + \left(\frac{\sigma_3}{c}\right) \sec \phi}\right] \quad (2)$$

$$\phi_e = \arcsin(1 - R_f + R_f \csc \phi_a)^{-1} \quad (3)$$

where

ϕ_a = adjusted friction angle

ϕ_e = equivalent friction angle

c = cohesion of soil

R_f = failure ratio (generally from 0.7 to 1.0)

$$= \frac{(\sigma_1 - \sigma_3)_{\text{failure}}}{(\sigma_1 - \sigma_3)_{\text{ultimate}}}$$

The support delay length X , which is the distance from the tunnel face to the leading edge of the lining, should be taken from the face of the tunnel rather than from the tail of the shield due to the existence of gap between the shield and soil. Ward (1969) and Belshaw and Palmer (1978) also observed that the use of a shield did not prove to be effective to reduce ground movements. However, the support delay length can be taken from the tail of the shield such as the case of Ashford tunnel because the average diameter of the shield was only 0.5 cm larger than that of the lining (Tattersall et al., 1955). The support delay length for the SEM tunnel is suggested taking from the face to the location where the invert is closed.

Stress reduction factors can be obtained easily and reliably if Table 2 is used.

7.3 Suggested Methods for the Prediction of Lining Loads

Tunnels are divided into several types, depending on the soil behaviour around an excavation, a factor which is mainly controlled by construction methods, soil types, and tunnel depths. Tunnels are divided into two main groups depending on the tunnel depth. The classification is based on the fact that a certain minimum thickness is required for the construction of the lining up to a certain depth regardless of the soil loads. The deeper tunnels of the two, having a depth to centerline to diameter ratio greater than three, are further subdivided into three groups depending on whether the tunnels have positive face control or not.

A specific method or combination of two different methods is suggested for each type of tunnelling for the estimation of lining loads. The proposed method is strictly valid for tunnels in soil or soft rock with a ratio of tunnel depth to diameter up to 6 for tunnels constructed without face control and up to about 8 for tunnels with face control. However, the method may be used for slightly deeper tunnels than these as shown later in this chapter. The depth generally covers most urban tunnels. A point to be mentioned is that the calculated lining load is an average one. Therefore, to calculate lining loads for a combined lining system, lining loads should be divided according to Young's modulus and the area of each of these linings as explained in Sec. 3.3.1.

7.3.1 A Depth to Centerline to Diameter Ratio Up to Three

Stress reduction factors cannot be used reliably in such a shallow tunnel because arching may not be fully developed due to the shallow soil cover. Furthermore, the whole soil section located above the tunnel crown can directly exert pressure on the tunnel lining because the plastic zone may be extended to the ground surface. Therefore, Peck's or Einstein and Schwartz's method without taking into account stress reduction factors is probably good enough for the prediction of lining loads in a shallow tunnel.

In addition, the minimum thickness for cast-in-place concrete linings is generally controlled by the clearance between the initial support ribs and the interior form required for the concrete.

The predicted lining loads may be too conservative if arching develops around an excavation. However, because the soil behaviour is rather uncertain due to the shallow soil cover, and the minimum practical thickness is usually enough for tunnels, the conservative estimate does not create problems.

Lining loads for tunnels constructed using the cut and cover method can also be estimated using Peck's method without taking into account stress reduction factors because the ground acts passively as a dead load, a loading condition which is similar to that of Peck's.

7.3.2 A Tunnel Depth to Diameter Ratio Greater than Three

7.3.2.1 No Face Control

Eisenstein and Negro (1985) suggested that the stress reduction factor (α) found using their method could be used, coupled with any analytical solution, for calculation of thrust forces and bending moments. The stress reduction factor can be accounted for through the use of a reduced unit weight of the soil. However, the method is strictly valid for stable ground due to the assumption of linear elastic ground and an unlined opening for the finding of the stress release factor as mentioned in Sec. 7.2.

The stress reduction factor can be obtained from Table 2 and combined with Einstein and Schwartz's method to calculate the lining loads for tunnels constructed according to the modern tunnelling philosophy and without the positive face control.

The average support thrust T_{av} can be expressed as follows according to Einstein and Schwartz's method:

$$T_{av} = \frac{1}{2} P_o R (1 + K_o) (1 - a_o)$$

$$a_o = \frac{CF(1 - \nu)}{C + F + CF(1 - \nu)}$$

$$C = \frac{ER(1 - \nu_1^2)}{E_1 A_1 (1 - \nu^2)} \quad F = \frac{ER^3(1 - \nu_1^2)}{E_1 I_1 (1 - \nu^2)}$$

where

C = compressibility ratio

F = flexibility ratio

A_1 = average cross-sectional area of the support per unit tunnel length and

P_o = vertical ground stress at the centre line of a tunnel.

It is customary to express soil loads on tunnels either in terms of the percentage of overburden pressure or in the form of:

$$P = n\gamma D$$

or
$$n = \frac{P}{\gamma D}$$

where

n = a dimensionless factor that depends on soil type and tunnelling method.

Then

$$\begin{aligned} n &= \frac{2T_{av}}{R(1 + K_o)\gamma D} \\ &= \frac{P_o(1 - a_o)}{\gamma D} \\ &= \frac{\gamma_{red}H(1 - a_o)}{\gamma D} \end{aligned}$$

where

γ_{red} = reduced unit weight of the soil caused by stress release around a tunnel
 H = depth to tunnel centerline.

Since

$$\frac{\gamma_{red}}{\gamma} = (1 - \alpha)$$

therefore

$$n = \frac{H(1 - a_o)(1 - \alpha)}{D} \quad (7.1)$$

7.3.2.2 Positive Face Control with Compressed Air or Fluids

Positive face control is necessary to maintain face stability and to prevent any excessive deformation at the face by allowing a limited amount of stress release to occur. Therefore, compressed air or slurry pressure is generally applied near the face. The pressure should be lower than the overburden pressure to prevent any possible blow-out. Eisenstein and Ezzeldine (1992) recommended applying about 40 % of the overburden pressure for a tunnel in Edmonton constructed using a hydroshield boring machine. Since less than overburden pressure is usually applied to the face, there should be a certain amount of stress release at the time of lining installation.

Deere et al. (1969) presented a ground reaction curve which showed the effect of air pressure. They assumed that the in-situ stress was reduced by the magnitude of the air pressure and that the lining load would increase again upon removal of the air pressure. However, they did not show how to evaluate the radial displacements of the tunnel wall at the time of lining installation. Negro (1988) suggested reducing the tunnel depth equivalent to the magnitude of the air pressure. However, he did not consider the stress increase on the lining after the removal of the air pressure.

It is obvious that the amount of stress release at the tunnel wall is reduced at the time of lining installation due to the positive face control compared to that of a tunnel constructed without face control. However, the amount of stress release is unknown. Deere et al. and Negro's concepts can be combined to evaluate the effect of positive face control on the lining loads. First, in-situ stresses are reduced by the magnitude of the air or slurry pressure. The reduction of in-situ stresses is achieved by reducing the soil cover depth above a tunnel. The stress reduction factor can be found as explained in the previous section but using the reduced soil depth. The stress acting on the lining before the removal of the air or slurry pressure can be found by multiplying the reduced unit weight of the soil by the reduced soil depth. The air or slurry pressure should be added to the stress found above to obtain the final stress acting on the lining upon removal of the air or slurry pressure.

Eq. (7.1) should be modified to take into account all of these factors described above. It was shown that n can be expressed as follows:

$$n = \frac{P_o(1 - a_o)}{\gamma D}$$

Since

$$\frac{P_i}{\gamma} = H_{eq}$$

Therefore

$$\begin{aligned} n &= \frac{[\gamma_{red}(H - H_{eq}) + P_i](1 - a_o)}{\gamma D} \\ &= \frac{\gamma_{red}(H - H_{eq})(1 - a_o)}{\gamma D} + \frac{P_i(1 - a_o)}{\gamma D} \\ &= \frac{(1 - \alpha)(H - H_{eq})(1 - a_o)}{D} + \frac{P_i(1 - a_o)}{\gamma D} \end{aligned} \quad (7.7)$$

where

P_i = air or slurry pressure

H_{eq} = soil depth equivalent to P_i .

Therefore, the dimensionless factor n for a tunnel constructed using air or slurry pressure can be estimated using Eq. (7.7).

7.3.2.3 Positive Face Control using Jet-Grouted Piles

If a tunnel is driven through unstable material such as loose sand, jet-grouted piles should be used prior to tunnelling to enhance face stability during the tunnelling operation. In this case, higher soil strength should be used, especially in terms of Young's modulus, for the calculation of the lining loads considering the use of jet-grouted piles. The low lining loads may be a result of the fillcreting operations used in the tunnel. Calculated lining loads will be lower than those measured if the increase of soil strength is not considered for the prediction of lining loads. In summary, Eq. (7.1) is applicable for tunnels belonging to this group to estimate the dimensionless factor n but with the increased Young's modulus considering the use of jet-grouted piles.

7.4 Verification of the Proposed Method Using Case Histories

There are several basic requirements of a good design method. First, the design method should be simple to use. Second, the design method should consider the stress release occurring before the installation of a liner in some way. Third, the method should take into account the plastic behaviour of the ground as well as that of elastic ground. The proposed method totally satisfies the first two conditions and partly satisfies the third conditions due to the assumption of stable ground used for the development of the stress reduction factors. However, the most important factor to be a good design method should be the accuracy of the predicted lining loads. Therefore, the measured and calculated lining loads are compared in this section to check the validity of the proposed design method.

Fourteen case histories were collected to verify the proposed method. These case histories are summarized in Appendix 1. The ratios of tunnel depth to tunnel diameter, H/D , considered were from 1.2 to 17.9, even though the method was not recommended for use in tunnels having a H/D greater than 6.

The proposed lining loads were compared with measured loads as shown in Figure 9. The stress reduction factor was not considered for tunnels having a ratio of H/D of less than three as suggested in Sec.7.3.1. The predicted lining loads for these shallow tunnels, i.e., Tunnel Nos. 2, 8, 9, and 11, were conservative, as expected. However, the conservative estimate does not create problems because the minimum practical thickness of the lining usually governs the tunnel design. The figure also

shows that the lining loads in Nipawin drainage tunnel No. 7 are very much underestimated. One of the possible reasons for this could be related to the fact that the space between the soil and lining was not fully filled. Matheson et al. (1986) stated that the volume of pea gravel injected into the gap between the soil and lining was about 80 % of the annular void. If the soil moved into the lining due to the existence of the gap behind the lining, the assumption of stable ground used for the development of the stress reduction factors could not be justified. However, the proposed method generally gives good approximations of the lining loads for most of the tunnels located in places other than Edmonton as shown in Figure 9.

7.5 Summary and Conclusions

An improved design method was proposed in this chapter using the existing design methods. A method for determining the stress reduction factors was also described. The values of the stress reduction factors for the different soil strengths, tunnel depths, and in-situ ratios were presented as tables. A specific method or combination of two different methods was suggested for the estimation of lining loads for various conditions of tunnelling.

Tunnels were divided into two main groups depending on the tunnel depth. For a shallow tunnel having a depth to centerline to diameter ratio up to three, Peck's or Einstein and Schwartz's method without taking into account stress reduction factor was suggested for the prediction of lining loads. Lining loads for tunnels constructed using the cut and cover method can also be estimated using Peck's method without taking into account stress reduction factors.

Deep tunnels, having a depth to centerline to diameter ratio greater than three, were further subdivided into three groups depending on whether the tunnels have positive face control or not. For a tunnel constructed without face control, the stress reduction factors could be used coupled with Einstein and Schwartz's method for the estimates of lining loads. The stress reduction factors can be easily obtained using Table 2. Typical values of nD/H for tunnels in Edmonton were obtained from parametric analyses. The calculated values of n from the table were slightly more conservative than those from the suggested equation. However, the table can still be used for quick estimations of lining loads for tunnels in Edmonton.

For a tunnel constructed with compressed air, the reduced soil depth, considering the air pressure, was used for the calculation of the stress reduction factors. Einstein and Schwartz's method was also suggested for estimating the lining loads. The air pressure should be added to the stress found above to obtain the final stress acting on the lining upon removal of the air pressure. It was also observed that increased soil strength, especially in terms of Young's modulus, should be used for the calculation of the lining loads for a tunnel constructed with positive face control using jet-grouted piles.

Finally, the loads calculated using the proposed method were compared with field measurements collected from various tunnels in terms of soil types and construction methods to verify the method. The proposed method gave reasonable approximations of the lining loads for tunnels in Edmonton and other areas, considering the accuracy of the load measurements, limited knowledge of ground and lining properties, and the existence of possible gaps between the lining and ground. Therefore, the proposed method can be used reliably for the estimation of lining loads of a tunnel. The stress reduction factors can be included for the estimates of the lining loads if the tunnel has a stability ratio less than 2 or is constructed according to modern tunnelling philosophy in which displacements are controlled.

There have been no absolute methods which can be used for estimating lining loads for all the various conditions of tunnelling in terms of the ground and construction methods. The author does not believe that such a method will be developed even in the future because the prediction of lining loads requires accurate information on the ground and lining properties, which is not always possible to obtain and which often varies along the tunnel section. Furthermore, the lining loads are affected by construction procedures, which also vary from one project to another depending on the tunnelling practice of the region and the skill of the tunnel builders. In other words, tunnelling is really an art rather than a science due to the nature of the ground and construction procedures. Therefore, the proposed method is recommended as an approximate guideline for the design of tunnels, but the results should be confirmed by field measurements. This is the reason that in-situ monitoring should be an integral part of the design procedure.

8. References

- Attewell, P. B. and El-Naga, N. M. A., 1977. Ground-Lining Pressure Distribution and Lining Distortion in Two Tunnels Driven Through Stiff, Stony/Laminated Clay. *Ground Engineering*, Vol. 10. No. 3, April, pp. 28-35.
- Attewell, P. B. and Farmer, I. W., 1974 (a). Ground Deformations Resulting from Shield Tunnelling in London Clay. *Canadian Geotechnical Journal*, Vol. 11, pp. 380-395.
- Attewell, P. B. and Farmer, I. W., 1974 (b). Ground Disturbance Caused by Shield Tunnelling in a Stiff, Overconsolidated Clay. *Engineering Geology*, Vol. 8, pp. 361-381.
- Barlow, J. P., 1986. Interpretation of Tunnel Convergence Measurements. M. Sc. Thesis, Department of Civil Engineering, University of Alberta, Edmonton, 235 p.
- Barratt, D. A. and Tyler, R. G., 1976. Measurements of Ground Movement and Lining Behaviour on the London Underground at Regents Park. TRRL Laboratory Report 684, Transport and Road Research Laboratory, Crowthorne, Berkshire.
- Barton, N, Lien, R., Lunde, J., 1974. Engineering Classification of Rock Masses for the Design of Tunnel Support. *Rock Mechanics*, Vol. 6, No. 4, pp. 189-236.
- Bathe, K. J., 1978. ADINA: A Finite Element Program for Automatic Dynamic Incremental Nonlinear Analysis. Report 82448-1, Massachusetts Institute of Technology, 385 p.
- Beaulieu, A. C., 1972. Tunnelling Experiences, City of Edmonton, Alberta, Canada. Proceedings, North American Rapid Excavation and Tunneling Conference. American Institute of Mining Engrs., Vol.2, pp.933-964.
- Belshaw, D. J. and Palmer J. H. L., 1978. Results of a Program of Instrumentation involving a Precast Segmented Concrete-Lined Tunnel in Clay. *Canadian Geotechnical Journal*, Vol. 15, pp. 573-583.
- Bieniawski, Z. T., 1976. Rock Mass Classifications in Rock Engineering. Proc. Symp. Exploration for Rock Engineering, pp. 97-106.
- Bieniawski, Z. T., 1984. *Rock Mechanics Design in Mining and Tunnelling*. A. A. Balkema, 272 p.
- Branco Jr., P., 1981. Behavior of a Shallow Tunnel in Till. M. Sc. Thesis, Department of Civil Engineering, University of Alberta, Edmonton, Alberta, 351 p.

- Branco, P. and Eisenstein, Z., 1985. Convergence-Confinement Method in Shallow Tunnels. Proceedings of 11th International Conf. on Soil Mech. and Found. Eng., San Francisco, Aug., Vol.4, pp.2067-2072.
- Broms, B. B. and Bennermark, H., 1967. Stability of Clay at Vertical Openings. Journal of the Soil Mechanics and Foundations Division, Proceedings of the American Society of Civil Engineers, pp. 71-94.
- Brown, E. T., Bray, J. W., Ladanyi, B. and Hoek, E., 1983. Ground Response Curves for Rock Tunnels. Journal of Geotechnical Engineering, Vol. 109, No. 1, pp. 15-39.
- Burke, H. H., 1960. Garrison Dam Test Tunnel, Investigation and Construction. Transactions, ASCE, Vol. 125, pp. 230-267.
- Chan, D., 1985. Finite Element Analysis of Strain Softening Materials. Ph. D. Thesis, Department of Civil Engineering, University of Alberta, Edmonton, Alberta, 355 p.
- Chen, W. F. and Mizuno, E., 1990. Nonlinear Analysis in Soil Mechanics, Theory and Implementation. Elsevier, 661 p.
- Chen, W. F. and Zhang, H., 1991. Structural Plasticity, Theory, Problems, and CAE Software. Springer-Verlag.
- Christian, J. T., 1980. The Application of Generalized Stress-Strain Relations, In: Application of Plasticity and Generalized Stress-Strain in Geotechnical Engineering. Proceedings of the Symposium on Limit Equilibrium, Plasticity and Generalized Stress Strain Applications in Geotechnical Engineering, Florida, ASCE, pp. 182-204.
- Cooley, P., 1982. Wedge-Block Tunnels in Water Supply. Journal of the Institution of Water Engineers and Scientists, Vol. 36, No. 1, pp. 9-26.
- Cooling, L. F. and Ward, W. H., 1953. Measurements of Loads and Strains in Earth Supporting Structures. Proceedings of the 3rd International Conference on Soil Mechanics and Foundation Engineering, Zurich, Vol. 2, pp. 162-166.
- Corbett, I., 1984. Load and Displacement Variations along a Soft Ground Tunnel. M. Sc. Thesis, Department of Civil Engineering, University of Alberta, Edmonton, Alberta, 246p.
- Cording, E. J., Hendron, A. J., and Deere, D. U., 1971. Rock Engineering for Underground Caverns, Proceedings, Symposium on Underground Rock Chambers, ASCE National Meeting on Water Resources Engineering, Phoenix, Arizona, pp. 567-600.

- Cording, E. J., Hendron, A. J., MacPherson, H. H., Hansmire, W. H., Jones, R. A., Mahar, J. W., and O'Rourke, T. D., 1975. Methods for Geotechnical Observations and Instrumentation in Tunneling. Report Prepared for U.S. National Science Foundation, Washington, D. C., Vol. 1, 2, 566 p.
- Craig, R. N. and Muir Wood, A. M., 1978. A Review of Tunnel Lining Practice in the United Kingdom. Transport and Road Research Laboratory, Suppl. Report 335, 211 p.
- Cronin et al., 1962. Discussion on the Thames-Lee Tunnel Water Main. Proceedings, Institution of Civil Engineers, Vol. 23, pp. 690-704.
- Curtis, D. J., 1976. Discussion of: Muir Wood, A. M., The Circular Tunnel in Elastic Ground. Geotechnique, Vol. 26, No. 2, pp. 231-237.
- Curtis, D. J., Lake, L. M., Lawton, W. T., and Crook, D. E., 1976. In-situ Ground and Lining Studies for the Channel Tunnel Project. Proceedings, Symposium, Tunnelling '76, London, pp. 231-242.
- Cuthbert, E. W. and Wood, F., 1962. The Thames-Lee Tunnel Water Main. Proceedings, Institution of Civil Engineers, Vol. 21, pp.257-276.
- Daemen, J. J. K., 1975. Tunnel Support Loading Caused by Rock Failure. Ph. D. Thesis, University of Minnesota, Minneapolis.
- Daemen, J. J. K. and Fairhurst, C., 1972. Rock Failure and Tunnel Support Loading. Proceedings, International Symposium on Underground Openings, Lucerne, pp. 356-369.
- Dar, S. M. and Bates, R. C., 1974. Stress Analysis of Hollow Cylindrical Inclusions. Journal of the Geotechnical Engineering Division, ASCE, Vol. 100, No. GT2, pp. 123-138.
- Davis, E. H., Gunn, M. J., Mair, R. J., and Seneviratne, H. N., 1980. The Stability of Shallow Tunnels and Underground Openings in Cohesive Material. Geotechnique, Vol. 30, No. 4, pp. 397-416.
- Deere, D. U., Peck, R. B., Monsees, J. E. and Schmidt, B., 1969. Design of Tunnel liners and support systems. Report for U. S. Department of Transportation, Office of High Speed Ground Transportation, Contract No. 3-0152, 287 p.
- DeLory, F. A., Crawford, A. M., and Gibson, M. E. M., 1979. Measurements on a Tunnel Lining in very Dense Till. Canadian Geotechnical Journal, Vol. 16, pp. 190-199.

- Desai, C. S. and Siriwardane, H. J., 1984. Constitutive Laws for Engineering Materials with Emphasis on Geologic Materials. Prentice-Hall, Inc., 468 p.
- Duddeck, H., 1980. On the Basic Requirements for Applying the Convergence-Confinement Method. *Underground Space*, Vol. 4, No. 4, pp. 241-247.
- Duddeck, H. and Erdmann, J., 1985. On Structural Design Models for Tunnels in Soft Soil. *Underground Space*, Vol. 9, pp. 246-259.
- Duddeck, H., Meister, D., Werner, E., Schlegel, R., and Theurer, M., 1979. Road Tunnel in very Soft Soil in Terrace Deposits in the Harz Mountains, Germany. *Tunnelling '79*, pp. 205-215.
- Duncan, J. M. and Chang, C. Y., 1970. Nonlinear Analysis of Stress and Strain in Soils. *Journal of the Soil Mechanics and Foundations Division, ASCE*, Vol. 96, No. SM 5, pp. 1629-1654.
- Duncan, J. M., Byrne, P., Wong, K. S. and Mabry, P., 1980. Strength, Stress-Strain and Bulk Modulus Parameters for Finite Element Analyses of Stresses and Movements in Soil Masses. Report No. UCB/GT/80-01, Department of Civil Engineering, University of California, Berkeley, 70 p.
- Dunnicliff, C. J., 1971. Equipment for Field Deformation Measurements. *Proceedings, Fourth Pan American Conference on Soil Mechanics and Foundation Engineering*, Vol. 2, pp. 319-332.
- Dunnicliff, J., 1988. *Geotechnical Instrumentation for Monitoring Field Performance*. John Wiley & Sons, 577 p.
- EBA Engineering Consultants Ltd., 1988. Preliminary Engineering Report-South Tunnel, SLRT Phase II. Submitted to The City of Edmonton and Stanley Associates Engineering Ltd.
- EBA Engineering Consultants Ltd., 1991. Contract Completion Report-South Bank Tunnels, SLRT Phase II. Submitted to The City of Edmonton and Stanley Associates Engineering Ltd.
- Egger, P., 1980. Deformations at the Face of the Heading and Determination of the Cohesion of the Rock Mass. *Underground Space*, Vol. 4, No. 5, pp. 313-318.
- Einstein, H. H. and Schwartz, C. W., 1979. Simplified Analysis for Tunnel Supports. *Journal of the Geotechnical Engineering Division, ASCE*, Vol. 105, No. GT4, pp. 499-518.

- Einstein, H. H. and Schwartz, C., 1980. Discussion on Simplified Analysis for Tunnel Supports. *Journal of the Geotechnical Engineering Division, ASCE*, No. GT7, pp.835-838.
- Eisenstein, Z., 1982. The Contribution of Numerical Analysis to Design of Shallow Tunnels. *Proceedings, International Symposium on Numerical Models in Geomechanics, Zurich*.
- Eisenstein, Z., 1992. Rock Engineering Class Notes. Department of Civil Engineering, University of Alberta.
- Eisenstein, Z. and Branco, P., 1990. Convergence-Confinement Method in Shallow Tunnels. *Canadian Tunnelling, Tunnelling Association of Canada*, pp. 77-83.
- Eisenstein, Z. and Kuwajima, F. M., 1990. Stress Measurements by Flat-Jack Method in the Shotcrete Lining of the SLRT South Tunnel. Report for the City of Edmonton and EBA Engineering Consultants Ltd., 18 p.
- Eisenstein, Z. and Negro Jr., A., 1985. Comprehensive Design Method for Shallow Tunnels. *ITA/AITES International Conference, Underground Structures in Urban Areas, Prague*, pp. 3-20.
- Eisenstein, Z. and Negro Jr., A., 1990. Integrated Design Method for Shallow Tunnels in Soft Ground. Presented at the JTA Tunnel Symposium in Tokyo, Japan, Vol. 2, pp.27-36.
- Eisenstein, Z. and Thomson, S., 1978. Geotechnical Performance of a Tunnel in Till. *Canadian Geotechnical Journal*, Vol. 15, pp.332-345.
- Eisenstein, Z., El-Nahhas, F., and Thomson, S., 1979. Pressure-Displacement Relations in Two Systems of Tunnel Lining. *Proceedings of 6th PanAmerican Conference on Soil Mechanics, Lima*, pp. 85-94.
- Eisenstein, Z., El-Nahhas, F., and Thomson, S., 1981. Strain Field around a Tunnel in Stiff Soil. Presented for 10th International Conference on Soil Mechanics and Foundation Engineering, Session 2: Tunnelling in Soils, Stockholm.
- Eisenstein, Z., Heinz, H. and Negro, A., 1984. On Three-Dimensional Ground Response to Tunnelling. *ASCE. Geotech III, Tunnelling in Soils and Rocks, Atlanta*, pp. 107-127.
- Eisenstein, Z., Kulak, G. L., MacGregor, J. G., and Thomson, S., 1977. Report on Geotechnical and Construction Performance of the Twin Tunnels. Unpublished Report

Prepared for The City of Edmonton Engineering Department, Edmonton, Alberta, 75 p.

Eisenstein, Z., Kuwajima, F. M. and Heinz, H. K., 1991. Behaviour of Shotcrete Tunnel Linings. Proceedings, Rapid Excavation and Tunnelling Conference, Seattle, pp. 47-57.

Eisenstein, Z., Thomson, S., and Branco Jr., P., 1982. South LRT Extension Jasper Avenue Twin Tunnel-Instrumentation test section at 102nd Street. Part I : Southbound Tunnel. Unpublished Report Submitted to The City of Edmonton, Edmonton, Alberta, 330 p.

El-Nahhas, F., 1977. Field Measurements in Two Tunnels in the City of Edmonton. M. Sc. Thesis, Department of Civil Engineering, University of Alberta, Edmonton, Alberta, 85 p.

El-Nahhas, F., 1980. The Behavior of Tunnels in Stiff Soils. Ph. D. Thesis, Department of Civil Engineering, University of Alberta, Edmonton, Alberta, 305 p.

Fenner, R., 1938. Untersuchungen zur Erkenntnis des Gebirgsdruckes. Gluckauf, Vol. 74, Essen, pp. 681-695 and 705-715.

GEO-SLOPE International Ltd., 1995. User's Guide for SIGMA/W Stress and Deformation Analyses. GEO-SLOPE International Ltd., Calgary, Alberta, Canada.

Gesta, P., Kerisel, J., Londe, P., Louis, C., and Panet, M., 1980. Tunnel Stability by Convergence-Confinement Method. Underground Space, Vol. 4, No. 4, pp. 225-232.

Ghaboussi, J. and Ranken, R. E., 1977. Interaction Between Two Parallel Tunnels. International Journal for Numerical and Analytical Methods in Geomechanics, Vol. 1, pp. 75-103.

Ghaboussi, J., Hansmire, W. H., Parker, H. W., and Kim, K. J., 1983. Finite Element Simulation of Tunneling Over Subways. Journal of Geotechnical Engineering, ASCE, Vol. 109, No. 3, pp. 318-334.

Harris, M. C. and Papanicolas, D., 1983. South LRT Extension Geotechnical Report No. 16, Corona Station Instrumentation Program. Report Submitted to Edmonton Transit-LRT Project, 39 p.

Hartmann, F., 1970. Elastizitätstheorie des ausgekleideten Tunnelhohlraumes und des eingebohrten kreisförmigen Rohres. Strasse Brücke Tunnel 22 (1970), Heft 8, 209-215, Heft 9, 241-246, und Jg. 24 (1972), Heft 1, 13-20, Heft 2, 39-45.

- Heinz, H. K., 1984. Applications of the New Austrian Tunnelling Method in Urban Areas. M.Sc. Thesis, Department of Civil Engineering, University of Alberta, 323 p.
- Hewett, B. H. M. and Johannesson, S., 1922. Shield and Compressed Air Tunneling. McGraw Hill, New York.
- Hoek, E., 1982. Geotechnical Considerations in Tunnel Design and Contract Preparation. Tunnelling'82, Sir Julius Wernher Memorial Lecture, IMM, Transactions, pp. A101-109
- Hoek, E. and Brown, E. T., 1980. Empirical Strength Criterion for Rock Masses. Journal of the Geotechnical Engineering Division, ASCE. Vol. 106, No. GT9, pp. 1013-1035.
- Hoek, E. and Brown, E. T., 1980. Underground Excavations in Rock. The Institution of Mining and Metallurgy, London, 527 p.
- Howells, M., 1980. Analysis of Tunnel Stability by the Convergence-Confinement Method. Underground Space, Vol. 4, No. 6, pp. 368-369.
- Hutchinson, D. E., 1982. Effects of Construction Procedure on Shaft and Tunnel Performance. M.Sc. Thesis, Department of Civil Engineering, University of Alberta, 267 p.
- International Tunnelling Association Working Group on General Approaches to the Design of Tunnels, 1988. Guidelines for the Design of Tunnels. Tunnelling and Underground Space Technology, Vol. 3, No. 3, pp. 237-249.
- Kaiser, P. K., 1980. Effect of Stress-history on the Deformation Behaviour of Underground Openings. 13th Canadian Rock Mechanics Symposium, CIM Special Volume 22, pp. 133-140.
- Katzenbach, R. and Breth, H., 1981. Nonlinear 3-D Analysis for NATM in Frankfurt Clay. Proceedings of the Tenth International Conference on Soil Mechanics and Foundation Engineering, Stockholm, Vol. 1, pp. 315-318.
- Kawamoto, T. and Okuzono, K., 1977. Analysis of Ground Surface Settlement Due to Shallow Shield Tunnels. International Journal For Numerical and Analytical Methods in Geomechanics, Vol. 1, pp. 271-281.
- Kerisel, J., 1980. Commentary on the General Report. Underground Space, Vol. 4, No. 4, pp. 233-239.

- King, H. J., Whittaker, B. N., and Batchelor, A. S., 1972. The Effects of Interaction in Mine Layouts. Fifth International Strata Control Conference, London, Paper 17, pp. 1-11.
- Kondner, R. L., 1963. Hyperbolic Stress-Strain Response: Cohesive Soils. Journal of the Soil Mechanics and Foundation Division, ASCE, Vol. 89, No. SM 1, pp. 115-143.
- Kuesel, T. R., 1987. Principles of Tunnel Lining Design. Tunnels and Tunnelling, pp. 25-28.
- Kulhawy, F. H., 1974. Finite Element Modeling Criteria for Underground Openings in Rock. Int. J. Rock Mech. Min. Sci. & Geomech. Abstr., Vol. 11, pp. 465-472.
- Kulhawy, F. H., 1977. Embankments and Excavations. In: Numerical Methods in Geotechnical Engineering (edited by Desai, C. S. and Christian, J. T.), McGraw Hill, pp. 528-555.
- Kuwajima, F. M., 1991. Behavior of Shotcrete in Shallow Tunnels. Ph. D. Thesis, Department of Civil Engineering, University of Alberta, Edmonton, 511 p.
- Ladanyi, B., 1974. Use of the Long-Term Strength Concept in the Determination of Ground Pressure on Tunnel Linings. Proceedings of the Third International Congress on Rock Mechanics, Denver, Vol. 2B, pp. 1150-1156.
- Ladanyi, B., 1980. Direct Determination of Ground Pressure on Tunnel Lining in a Non-Linear Viscoelastic Rock. Underground Rock Engineering, 13th Canadian Rock Mechanics Symposium, Toronto, CIM Special Vol. 22, pp. 126-132.
- Lane, K. S., 1960. Garrison Dam Test Tunnel, Evaluation of Test Results. Transactions, ASCE, Vol. 125, pp. 268-306.
- Lane, K. S., 1975. Field Test Sections-Save Cost in Tunnel Support. Report from Underground Construction Research Council, American Society of Civil Engineers, 59 p.
- Lombardi, G., 1970. The Influence of Rock Characteristics on the Stability of Rock Cavities. Tunnels and Tunnelling, Vol. 2, No. 1, pp. 19-22, and Vol. 2 No. 2, pp. 104-109.
- Lombardi, G., 1973. Dimensioning of Tunnel Linings with regard to Construction Procedure. Tunnels and Tunnelling, Vol. 5, pp. 340-351
- Lombardi, G., 1980. Some Comments on the Convergence-Confinement Method. Underground Space, Vol. 4, No. 4, pp. 249-258.

- Londe, M., 1980. Analysis of Tunnel Stability by the Convergence-Confinement Method. *Underground Space*, Vol. 4, No. 6, pp. 375-376.
- Matheson, D. S. and Rupprecht, H., 1985. The Nipawin Drainage Tunnel -Design and Construction. Presented at the CEA Hydraulic Power Section Meeting, Regina, Saskatchewan.
- Matheson, D. S., Macpherson, J. G., and Eisenstein, Z., 1986. Design and Construction Aspects of the Nipawin Drainage Tunnel. *Canadian Tunnelling*, pp. 59-73.
- Meister, D. and Wallner, M., 1977. Instrumentation of a Tunnel in Extremely Bad Ground and Interpretation of the Measurements. *International Symposium on Field Measurements in Rock Mechanics*, Zurich, pp. 919-933.
- Montgomery, C. J. and Eisenstein, Z., 1995. Soft Ground Tunnel Design in Edmonton. Unpublished Report Submitted to The City of Edmonton, Edmonton, Alberta, 198 p.
- Morton, J. D., Dunbar, D. D., Palmer, J. H. L., Use of a Precast Segmented Concrete Lining for a Tunnel in Soft Clay. *International Symposium on Soft Clay*, Bangkok, pp. 587-598.
- Muir Wood, A. M., 1969. Discussion of: Peck, R. B., Deep Excavations and Tunneling in Soft Ground. *Proceedings, 7th International Conference on Soil Mechanics and Foundation Engineering*, Vol. 3, pp. 363-367.
- Muir Wood, A. M., 1975. The Circular Tunnel in Elastic Ground. *Geotechnique* 25, No. 1, pp.115-127.
- Muir Wood, A. M. and Gibb, F. R., 1971. Design and Construction of the Cargo Tunnel at Heathrow Airport, London. *Proceedings, Institution of Civil Engineers*, Vol. 48, Jan., pp. 11-34.
- Negro, A. Jr., 1988. Design of Shallow Tunnels in Soft Ground. Ph. D. Thesis, Department of Civil Engineering, University of Alberta, Edmonton, 1480 p.
- Negro, A. and Eisenstein, Z., 1981. Ground Control Techniques Compared in Three Brazilian Water Tunnels. *Tunnels and Tunnelling*, Oct. pp. 11-14, Nov. pp. 52-54, Dec. pp. 48-50.
- O'Rourke, T. D., 1984. Guidelines for Tunnel Lining Design. *American Society of Civil Engineers*, 82 p.

- Oteo, C. S. and Sagaseta, C., 1982. Prediction of Settlements due to Underground Openings. Proceedings, International Symposium on Numerical Models in Geomechanics, Zurich, September, pp. 653-659.
- Panet, H., 1973. La stabilite des ouvrages souterrains-soutenement et revetement. Rapport de recherche No. 28. Paris:Laboratoires des Ponts et Chaussees.
- Panet, M., 1976. Stability Analysis of a Tunnel Driven in a Rock Mass Taking Account of the Post-Failure Behaviour. Rock Mechanics. Vol. 8, pp. 209-223.
- Panet, M. and Guenot, A., 1982. Analysis of Convergence Behind the Face of a Tunnel. Tunnelling '82, The Institution of Mining and Metallurgy, pp. 197-204.
- Paterson, M. S., 1978. Experimental Rock Deformation -The Brittle Field. Springer-Verlag, 254 p.
- Peck, R. B., 1969. Deep excavation and Tunneling in soft ground. Proceedings, 7th International Conference on Soil Mechanics and Foundation Engineering, Mexico, State-of-the-Art Volume, pp. 225-290.
- Peck, R. B., Hendron, A. J., and Mohraz, B., 1972. State of the Art of Soft-Ground Tunneling. RETC Proceedings, Vol. 1, pp.259-286.
- Pelli, F., 1987. Near Face Behavior of Deep Tunnels in Rock. Ph.D Thesis, Department of Civil Engineering, University of Alberta, 406 p.
- Pelli, F., Kaiser, P. K., and Morgenstern, N. R., 1986. Three-Dimensional Simulation of Rock-Liner Interaction Near Tunnel Face. Symposium on Numerical Models in Geomechanics, Ghent, pp. 359-368.
- Phelps, D. J. and Brandt, J. R., 1989. Design and Construction of Tunnels for the Edmonton LRT. Canadian Tunnelling, Tunnelling Association of Canada, pp.45-59.
- Plichon, J. N., 1980. Analysis of Tunnel Stability by the Convergence-Confinement Method. Underground Space, Vol. 4, No. 6, pp.384-388.
- Rabcewicz, L. V., 1969. Stability of tunnels under rock load. Water Power, June, pp.225-229; July, pp. 266-273; Aug, pp. 297-302.
- Ranken, R. E., 1978. Analysis of Ground-Liner Interaction for Tunnels. Ph.D. Thesis, Department of Civil Engineering, University of Illinois, 427p.
- Ranken, R. E. and Ghaboussi, J., 1975. Tunnel Design Considerations: Analysis of Stresses and Deformations around Advancing Tunnels. U.S. Department of Commerce, Springfield, Report UILU-ENG75-2016.

- Rocha, M., 1968. New Techniques for the Determination of the Deformability and State of Stress in Rock Masses. Proceedings, International Symposium on Rock Mechanics, Madrid, pp. 289-302.
- Rocha, M., Lopes, J. J. B., and da Silva, J. N., 1966. A New Technique for Applying the Method of the Flat Jack in the Determination of Stresses inside Rock Masses. Proceedings, First Congress of the International Society of Rock Mechanics, Lisbon, Vol. 2, pp. 57-65.
- Rowe, R. K., Lo, K. Y. and Kack, G. J., 1981. The Prediction of Subsidence above Shallow Tunnels in Soft Soil. Implementation of Computer Procedures and Stress-Strain Laws in Geotechnical Engineering, Vol. 1, pp. 266-280.
- Sauer, G. and Jonuscheit, P., 1976. Stress Redistribution in the Middle Wall Between Tubes of a Twin-Tunnel During Synchronous Excavation. Rock Mechanics. Vol. 8, pp. 1-22.
- Schmidt, B., 1984. Tunnel lining design - Do the theories work?. Fourth Australia - New Zealand Conference on Geomechanics, Perth, pp. 682-693.
- Schwartz, C. W. and Einstein, H. H., 1980 (a). Improved Design of Tunnel Supports: Vol. 1 - Simplified Analysis for Ground-Structure Interaction in Tunneling. Report No. UMTA-MA-06-0100-80-4, U.S. Department of Transportation, 427 p.
- Schwartz, C. W. and Einstein, H. H., 1980 (b). Simplified Analysis for Ground-Structure Interaction in Tunneling. The State of the Art in Rock Mechanics, Proceedings of the Twenty-First U. S. Symposium on Rock Mechanics, pp. 787-796.
- Soliman, E., Duddeck, H., and Ahrens, H., 1993. Two- and Three-dimensional Analysis of Closely Spaced Double-tube Tunnels, Tunnelling and Underground Space Technology, Vol. 8, No. 1, pp. 13-18.
- Sorensen, K. L., 1986. Tunnelling for the South LRT Extension in Edmonton, Alberta. 6th annual Canadian Tunnelling Conference, Niagara Falls, Ontario.
- Srivastava, R. K., Sharma K. G., and Varadarajan, A., 1988. Analysis of Stresses in the Pillar Zone of Twin Circular Interacting Tunnels. Numerical Methods in Geomechanics, pp. 1597-1606.
- Szechy, K., 1966. The Art of Tunnelling. Akademiai Kiado, Budapest, 891 p.

- Tan, D. Y. and Clough, G. W., 1980. Ground Control For Shallow Tunnels by Soil Grouting. *Journal of the Geotechnical Engineering Division, Proceedings of the American Society of Civil Engineers*, Vol. 106, No. GT.9, pp. 1037-1057.
- Tattersall, F., Wakeling, T. R. M., and Ward, W. H., 1955. Investigations into the Design of Pressure Tunnels in London Clay. *Institution of Civil Engineers Proceedings*, London, Vol. 4, Part 1, pp. 400-471.
- Terzaghi, K., 1943. *Theoretical Soil Mechanics*, Wiley, New York, pp. 194-197.
- Terzaghi, K., 1946. Rock Defects and Loads on Tunnel Supports; In: *Rock Tunneling with Steel Supports* by Proctor, R. V. and White, T. L., Commercial Shearing Co., Ohio, pp. 17-99.
- Thomas, H. S. H. and Ward, W. H., 1969. The Design, Construction and Performance of a Vibrating-Wire Earth Pressure Cell. *Geotechnique*, Vol. 19, No. 1, pp. 39-51.
- Thomson, S. and El-Nahhas, F., 1980. Field Measurements in Two Tunnels in Edmonton, Alberta. *Canadian Geotechnical Journal*, Vol. 17, pp. 20-33.
- Thomson, S., Martin, R. L. and Eisenstein, Z., 1982. Soft Zones in the Glacial Till in Downtown Edmonton. *Canadian Geotechnical Journal*, Vol. 19, pp. 175-180.
- Thurber Consultants Ltd., 1986. SLRT Extension-Phase II, Insitu Testing at the Proposed University Station Site. *Geotechnical Report No.3*, Submitted to The City of Edmonton.
- Tweedie, R. W., Harris, M. C., Gerber, G. E., and Eisenstein, Z., 1989. Ground and Structure Monitoring for the Edmonton SLRT-Phase II Tunnels. *Canadian Tunnelling*, pp.61-72.
- Uff, J. F., 1970. In Situ Measurements of Earth Pressure for a Quay Wall at Seaforth, Liverpool. *Proceedings of the Conference on In situ Investigations in Soil & Rock*, British Geotechnical Society, London, pp. 229-239.
- Ward, W. H., 1969. Discussion of: Peck, R. B., Deep Excavations and Tunneling in Soft Ground. *Proceedings, 7th International Conference on Soil Mechanics and Foundation Engineering*, Vol. 3, pp. 320-325.
- Ward, W. H., 1978. Ground Supports for Tunnels in Weak Rocks. *Geotechnique*, Vol. 28, No. 2, pp. 133-171.

- Ward, W. H. and Chaplin, T. K., 1957. Existing Stresses in Several Old London Underground Tunnels. Proceedings, Fourth International Conference on Soil Mechanics and Foundation Engineering, Vol. 2, pp. 256-259.
- Ward, W. H. and Pender, M. J., 1981. Tunnelling in Soft Ground - General Report. Proceedings of the Tenth International Conference on Soil Mechanics and Foundation Engineering, Stockholm, Vol. 4, pp. 261-275.
- Ward, W. H. and Thomas, H. S. H., 1965. The Development of Earth Loading and Deformation in Tunnel Linings in London Clay. Proceedings, Sixth International Conference on Soil Mechanics and Foundation Engineering, Vol. 2, pp. 432-436.
- Ward, W. H., Coats, D. J. and Tedd, P., 1976. Performance of Tunnel Support Systems in the Four Fathom Mudstone. Tunneling '76, London, pp. 329-340, disc. pp. 348-367.
- Ward, W. H., Samuels, S. G., and Muriel, E. B., 1959. Further Studies of the Properties of London Clay. Geotechnique, Vol. 9, No. 2, pp. 33-58.
- Weber, J., 1984. Experience using Compressed-Air Drivage and Shotcreting. Tunnel 1/84, pp. 16-27.
- Whittaker, B. N. and Bonsall, C. J., 1982. Design Aspects Relating to the Stability of Coal Mining Tunnels. First International Conf. on Stability in Underground Mining, SME Symp., Vancouver, pp. 519-534.
- Whittaker, B. N. and Frith, R. C., 1990. Tunnelling -Design, Stability and Construction. The Institution of Mining and Metallurgy, London, 460 p.
- Wong, R. C. K. and Kaiser, P. K., 1986. Interpretation of Performance of a Small Tunnel in Clayshale. Presented at the 39th Canadian Geotechnical Conference, Ottawa.
- Wood, D. F., Nickel, G. B. and Borch, N. G., 1989. Developments in the use of shotcrete for tunnel support. Proceedings of International Congress on Progress and Innovation in Tunnelling, ITA, Toronto, pp. 439-447.

Table 1 Primary Liner Loads in Edmonton Tunnels

Tunnel	Method	Ground	Depth* (H)	Dia.* (D)	H/D	Pv (KPa)	PL (KPa)	PL/Pv x 100 (%)	h (m)	n=h/D	Method of Measurements
A. Northeast Line	TBM	Till	10.2	6.1	1.7	214	169	79	8.05	1.3	(e)
B. LRT-South Extension	TBM	Till	11.8	6.2	1.9	248	52-64	21-26	2.48-3.07	0.40-0.49	(a)
SLRT-Phase II											
C. (Section B2)	TBM	Till	15.8	6.3	2.5	332	105	32	5.0	0.79	(a)
D. (Section C2)	SEM	Till	9.7	6.3	1.5	204	89.37	44	4.3	0.68	(b)
E. (Section A1)	TBM	Sand	17.2	6.3	2.7	361	46	13	2.19	0.35	(a)
F. Whitemud Creek	TBM	Clay Shale	47.2	6.05	7.8	991	140	14	6.67	1.10	(c)
G. 170th Street	TBM	Till	20	2.56	7.8	420	188	45	8.95	3.50	(d)
Experimental Tunnel											
H. (Section 1)	TBM	Till	27	2.56	10.5	567	103	18	4.9	1.92	(e)
I. (Section 2)	TBM	Till	27	2.56	10.5	567	219.6	39	10.46	4.08	(f)
J. (Section 3)	TBM	Till	24	2.56	9.4	504	135-156	27-31	6.40-7.44	2.50-2.9	(a)
Banks of North											
Saska. River											
K. (Section 1)	TBM	Till	13.7	3.2	4.3	288	26.9	9	1.28	0.40	(a)
L. (Section 2)	TBM	Till	13.7	3.2	4.3	288	14.2	5	0.68	0.21	(a)
M. (Section 4)	TBM	Sand	16.7	3.2	5.2	351	259.85	74	12.37	3.87	(a)

Notes: (a) From load cells

(b) From flat jack tests in the shotcrete liner

(c) From the deformation of the ribs

(d) From lagging deflection

(e) From the measurements of strains in the rib

(f) From the measurements of strains in the precast segmented liner

* units in meters

Table 2 Stress Reduction Factors Suggested for the Proposed Design Method
($3 \leq Z/D \leq 9$)

Ko	ϕ_e	X/D											
		0	0.1	0.2	0.25	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1.0 ≤
0.6	20	0.225	0.296	0.351	0.375	0.381	0.394	0.405	0.410	0.414	0.418	0.423	0.427
	30	0.268	0.379	0.466	0.504	0.514	0.535	0.554	0.561	0.568	0.575	0.582	0.589
	40	0.275	0.409	0.527	0.579	0.594	0.622	0.650	0.660	0.670	0.680	0.689	0.699
0.8	20	0.241	0.325	0.391	0.418	0.426	0.440	0.453	0.458	0.462	0.467	0.471	0.475
	30	0.255	0.361	0.448	0.487	0.497	0.518	0.537	0.544	0.551	0.558	0.565	0.572
	40	0.259	0.375	0.478	0.525	0.538	0.564	0.589	0.598	0.608	0.617	0.626	0.635
1.0	20	0.215	0.285	0.341	0.365	0.372	0.384	0.396	0.400	0.404	0.409	0.413	0.417
	30	0.229	0.314	0.388	0.422	0.432	0.450	0.468	0.475	0.482	0.488	0.495	0.501
	40	0.237	0.329	0.414	0.454	0.465	0.488	0.510	0.519	0.528	0.536	0.545	0.553




Figure 1 Measured and Calculated n for the Linings in Edmonton Tunnels




Figure 2 Measured and Calculated n for the Linings in Edmonton Tunnels Using Reduced Unit Weight





Figure 3 Two-Dimensional Meshes of the Experimental Tunnel



$$a_1 = L_1/6 \quad (\text{Contributing Area for a node 1})$$

$$a_2 = 4L_1/6 \quad a_3 = L_1/6 + L_2/6$$

$$a_4 = 4L_2/6 \quad a_5 = L_2/6$$




Figure 4 (a) Contributing Areas for Uniform Stresses
(b) Calculation of Equivalent Loads for Initial Stresses




Figure 5 Longitudinal Cross Section of the 3-D Mesh of the Experimental Tunnel




Figure 6 Comparison of Convergence Curves of Springline for Slices 5 and 6 without Liner




Figure 7 Comparison of Convergence Curves of Slice 5 for 2-D and 3-D Analyses




Figure 8 Convergence Curves for Slice 5 from 3-D Analyses with Liner Installation




Figure 9 Comparison of Predicted n Calculated using the Proposed Method with Measured n for the Tunnels Located other than Edmonton