불규칙 외란을 받는 유연한 계에 대한 "모드선택 퍼지제어』

윤영수[†](고려대)·김용관^{**}(국과연)·고광원^{*}(고려대)·여운주^{*}(고려대)·허 훈^{***}(고려대)

「Mode Selecting Fuzzy Controller」 to suppress the response of flexible system under irregular disturbance

Young-Soo Yoon, Yong-Kwan Kim, Kwang-Won Ko, Woon-Joo Yeo, and Hoon Heo

Keywords: Fuzzy control(퍼지 제어), Modal analysis(모달 해석), Irregular disturbance(불규칙 외란), Piezo actuator(압전소자 작동기), Flexible structure(유연한 구조체)

Abstract: A fuzzy logic controller design technique is proposed to apply to the control of flexible system under irregular disturbance. The fuzzy rules of 「Mode Selecting Fuzzy Controller」 are constructed using displacement, velocity information and modal characteristics of the system. The frequency information of flexible system is picked up from 「Mode Selecting Unit」 based on Fast-Fourier transform algorithm. Experiment is conducted to verify the proposed theoretical approach. Piezo ceramic and laser accelerometer are used as actuator and sensor in the experiments respectively.

한국소음진동공학회 2002년도 추계학술대회 강연 및 논문 초록집

KSNVE 02F036

PDP 모듈의 소음 저감

최수용* (삼성전자)·이석영*(삼성SDI)·주재만**·강정훈**·오상경**(삼성전자)

Noise Reduction of PDP Module

Sooyong Choi, Seokyeong Lee, Jaeman Joo, Junghun Kang, Sangkyoung

Key Words : : PDP, Circuit noise(회로소음), SMPS, Power MOSFET, Heat sink(방열핀), Condenser, Transforme

Abstract: A PDP(Plasma Display Panel) module consists of a discharge panel, a SMPS for power supply, driving boards for panel control, and a logic board. Driving boards supply high voltage pulses to induce glow dischargein the PDP panel. The electrical pulses excite the circuit elements and subsequentlyacoustic noises. The main sources of the noise in the circuit are the transformer of SMPS and the power MOSFET of driving boards, and the heat sinks often amplify the noise level. The reduction of the acoustic noises was achieved by modifying both the structural and circuit elements.