# The growth and structure of CNTs dependent on the catalysts using thermal CVD

Tae Jae Lee, Seung Chul Lyu, Sang Kyu Choi, and Cheol Jin Lee Dept. of Nanotechnology, Hanyang University, 17 Haengdang-dong, Seongdong-gu, Seoul, 133-791, Korea

Phone: +82-2-2293-4744, E-mail: cjlee@hanyang.ac.kr

Jin Ho Lee

Micro-electronics tech. Labs., ETRI, 161 Kajong-Dong, Yusong-Gu, Taejon, 305-350, Korea

#### **Abstract**

We have investigated the catalyst effect on the growth and structure of CNTs using thermal chemical vapor deposition. The respective growth rate of CNTs shows that the performance of catalysts is in the order of nickel (Ni)>cobalt (Co)>iron (Fe). The average diameter of CNTs follows the sequence of Fe, Co, and Ni catalysts. The structure of CNTs reveals almost same morphology regardless of catalyst but the crystallinity of CNTs is largely dependent on catalyst. The crystallinity of CNTs synthesized from Fe catalyst is higher than that from Ni or Co catalyst. We demonstrate that the growth rate, the diameter, and the crystallinity of CNTs can be manipulated by selecting the catalysts.

# 1. Introduction

Synthesis of carbon nanotubes (CNTs) has been extensively investigated by a number of research groups, since the first observation in 1991 [1]. Recently, the synthesis of CNTs using CVD method has attracted much attentions because of many advantages such as high purity, high yield, controlled growth, and vertical alignment.

The most effective catalysts for the CVD growth of CNTs are known to be iron (Fe), cobalt (Co), and nickel (Ni). The peculiar ability of these metals was suggested to relate to the catalytic activity for the decomposition of carbon precursors, the formation of meta-stable carbides, the diffusion of carbons, and the formation of graphitic sheets, *etc* [2,3]. Despite tremendous progress in synthesizing CNTs, the systematic study of the catalyst effect on the CNT growth is still not much reported yet. Recently, Ren *et al.* reported effect of catalyst on the growth of aligned carbon nanotubes using plasma-enhanced hot filament

CVD system [4]. Exact understanding of the catalyst activity would lead eventually a controlled growth of CNTs, which is prerequisite for various potential applications.

In this work, we report the effect of Fe, Co, and Ni catalysts on the CNTs synthesized by thermal CVD of acetylene (C<sub>2</sub>H<sub>2</sub>) gas. The CNTs were grown on three different catalyst particles under the same condition. The nanometer sized catalyst particles were formed by ammonia pretreatment [5]. The growth rate and structure of CNTs were fully optimized. The configuration and crystallinity of CNTs grown on Fe, Co, and Ni catalyst particles were investigated using scanning electron microscopy, transmission electron microscopy, thermo gravimetric analysis, and Raman spectroscopy.

## 2. Experimental

The 20 mm  $\times$  30 mm size p-type plane silicon (100) substrates with a resistivity of 15  $\Omega$ cm were thermally oxidized. A 50 nm-thick Fe (or Co, Ni) film was thermally deposited on the SiO<sub>2</sub> substrate using a thermal evaporator under a pressure of 10<sup>-6</sup> Torr. The catalyst deposited substrates were loaded on a quartz boat. Argon (Ar) was flowed into a quartz CVD reactor in order to prevent the oxidation of catalyst metal while raising the temperature. The catalyst films were pretreated by ammonia (NH<sub>3</sub>) gas with a flow rate of 100 sccm for 20 min at 950 °C in order to form the nanometer sized catalyst particles on the substrates. The catalyst films were etched by introducing NH<sub>3</sub> gas into the quartz reactor at 950 °C and were easily agglomerated on the substrates, resulting in nanometer sized particles. For the condition of NH<sub>3</sub> treatment at 950 °C, the diameter of Fe, Co, and Ni catalyst particles was in the range of 150-190 nm, 130-150 nm, and 120-130 nm, respectively. After formation of nanometer sized catalyst particles, the CNTs were sequently grown using  $C_2H_2$  with a flow rate of 30 sccm for 10 min at the same temperature. After finishing the CNT growth, the reactor was cooled down to room temperature under Ar ambient.

#### 3. Results and discussion

Fig. 1 shows SEM images of the CNTs grown on catalyst particles formed on the SiO<sub>2</sub> substrates using thermal CVD of acetylene for 10 min at 950 °C. The length of vertically aligned CNTs is 10 μm, 17 μm, and 20 μm for Fe, Co, and Ni catalyst deposited substrates, respectively. The average diameter of CNTs grown on Fe, Co, and Ni catalysts is 130 nm, 110 nm, and 100 nm, respectively. The density of CNTs is about ~4×10<sup>9</sup>, ~4×10<sup>9</sup>, and ~2×10<sup>9</sup>/cm<sup>2</sup> for Fe, Co, and Ni catalysts. These results are summarized in Table 1, showing that the growth rate, diameter, and density of CNTs are dependent on the catalyst.

From several experimental runs, the average growth rate of CNTs on Fe, Co, and Ni catalysts is measured as  $1\pm0.2$ ,  $1.7\pm0.3$ , and  $2\pm0.3$  µm/min, respectively. The maximum growth rate can be achieved when the Ni catalyst is used. The Fe catalyst renders the lowest growth rate among three catalysts. The growth rate mainly depend on the diffusion rate of carbons. We already reported that the growth rate of CNTs on the Fe catalyst increased by a factor of 4 as the temperature increased from 750 to 950 °C [6]. In our experiment, the growth rate increases as the growth temperature increases regardless of catalyst.




Figure 0. SEM micrographs for the vertically aligned CNTs grown on (a) Fe, (b) Co, and (c) Ni catalyst particles deposited SiO2 substrate, under the condition that C2H2 flows with a rate of 30 sccm for 10 min at 950 °C.

Catalyst type	Growth rate (μm/min)	Diameter distribution (nm)	Averaged diameter (nm)	Density (/cm²)
Fe	1±0.2	80-200	130	4×10 <sup>9</sup>
Co	$1.7\pm0.3$	80-130	110	4×10 <sup>9</sup>
Ni	2 ±0.3	90-110	100	2×10 <sup>9</sup>

Table 1. The growth rate, diameter, and density of CNTs grown on Fe, Co, and Ni catalysts using thermal CVD of C2H2 at 950 °C.

To understand the catalyst effect on the growth rate of CNTs, we evaluated a correlation between the diffusion rate of carbons and the relative growth rate of CNTs according to the catalysts at 950 °C. In bulk Fe, Co, and Ni metals, the diffusion coefficient of carbons is  $1.1 \times 10^{-7}$ ,  $8 \times 10^{-8}$ , and  $1.6 \times 10^{-7}$  cm<sup>2</sup>s<sup>-1</sup> at 950 °C, respectively [7]. Since the diffusion rate is usually proportional to the diffusion coefficient, the diffusion rate of carbons would follow the order Ni>Fe>Co. The growth rate of CNTs between Ni and Co catalysts is consistent with the diffusion rate in bulk Ni and Co metals. While the growth rate of CNTs reveals inverse sequence from the diffusion coefficients between Fe and Co catalysts. This result can be explained by the size effect of catalyst particles on the CNT growth. As the size of catalyst particle decreases, carbons adsorbed at the catalyst surface can arrive at the growth site at a shorter time, resulting in an increasing growth rate of CNTs. In this work, the size of Co catalyst particle is smaller than that of Fe catalyst particle. We suggest that the size effect of catalyst particles would be an another factor to determine the growth rate of CNTs beside the diffusion rate of carbon. Bower et al. also reported an inverse dependence of growth rate on the diameter of catalyst particles for the growth of CNTs on Co catalyst using plasma enhanced CVD [8].

In our result, the CNTs grown on Fe catalyst have a larger diameter and a broad diameter distribution compared with Co or Ni catalyst. We could find that the Fe catalyst particles had the largest diameter and the broadest size distribution among the three catalysts (Fe>Co>Ni) before the CNT growth. The lower density of CNTs grown on Ni catalysts is rationalized by the easy agglomeration of the small sized Ni particles compared with Fe or Co particles.

We measured TEM images of the CNTs to

investigate the structure dependence on the three catalysts. Fig. 2a-c show TEM images of the CNTs grown on Fe, Ni, and Co catalysts, respectively. The CNTs exhibit exclusively a multiwalled bamboo-like structure for all three catalysts. The CNTs have a closed tip without encapsulated catalyst particle and compartment layers with a curvature oriented to the closed tip. Fig. 2d-f show the HRTEM images for the wall of CNTs grown on Fe, Ni, and Co catalysts. The left and top of the images correspond to the outside of the wall and the tip of a nanotube, respectively. The graphitic sheets are separated by ~0.34 nm and are tilted with a few degree angles toward the tube axis [9]. The outer graphitic sheets of CNTs are less crystalline compared with the inner graphitic sheets for all three catalysts. The graphitic sheets of the CNT grown on Fe catalyst reveal highly ordered crystalline structure. The CNT grown on Ni catalyst has a little lower degree of crystalline perfection than that of Fe catalyst. On the other hand, the CNT grown on Co catalyst shows that the graphitic sheets are waved over a short range and thus are more defective structure compared with Fe or Ni catalysts. The HRTEM




Figure 2. TEM images for the bamboo-like structured CNTs grown on (a) Fe, (b) Ni, and (c) Co catalysts, showing the closed tip without encapsulated catalyst particles and the compartment layers with a curvature directed to the tip. HRTEM images for the graphitic sheets of CNTs grown on (d) Fe, (e) Ni, and (f) Co catalysts.

images reveal that the crystallinity of CNTs follows a sequence of Fe>Ni>Co.

Fig. 3 is a plot for the weight loss in % vs. the oxidation temperature, measured by heating up the CNTs in a TGA. The weight loss curve between 200 and 800 °C is plotted by adjusting about 100 % for the weight loss at 800 °C which is presumably the weight of catalyst (usually 10 % of total weight). The CNTs grown on Fe, Ni, and Co catalysts start to gasify at approximately 550, 550, and 500 °C, respectively. For pure graphite, the onset of gasification is observed at 700 °C under the same experimental conditions. The respective weight loss is measured in the range of 550-680 °C, 550-650 °C, and 500-620 °C for the CNTs grown on Fe, Ni, and Co catalysts, respectively. The TGA data indicate that the crystallinity of the CNTs grown on Fe catalyst is a little better than that of CNTs grown on Ni catalyst, but the CNTs grown on Co catalyst exhibit much less crystallinity compared with Fe or Ni catalysts.




Figure 3. TGA data of the weight loss in % vs. the oxidation temperature for the CNTs grown on Fe, Ni, and Co catalysts.

Fig. 4 shows Raman spectra for the CNTs grown on Fe, Ni, and Co catalysts. All spectra show mainly two Raman bands at ~1335 cm<sup>-1</sup> (D band) and ~1580 cm<sup>-1</sup> (G band). The linear relation between the inverse of the in-plane crystallite dimension and the intensity ratio of D band to G band (I(D)/I(G)) were noted [10]. In Fig. 4, the value of I(D)/I(G) for the CNTs grown on Fe, Ni, and Co catalysts is 0.8, 0.9, and 1.2, respectively. It reveals that the degree of crystalline perfection of the CNTs grown on Fe or Ni catalyst is higher than that of CNTs grown on Co catalyst, which is very consistent with the HRTEM images and TGA




Figure 4. Raman spectrum for the CNTs grown on Fe, Ni, and Co catalysts.

data. Recently, Ren et al. also reported that the CNTs grown on Ni catalyst using hot filament plasma CVD exhibited a higher degree of crystalline perfection than that of CNTs grown on Co catalyst [4]. From above results, we suggest that the crystallographic characteristics of catalyst particle play an important role in governing the crystallinity of CNTs, but further extensive studies will be necessary to provide a definite evidence for such possibility.

### 4. Conclusion

we have studied the catalyst effect on the growth and structure of the CNTs using thermal CVD. The growth rate of CNTs indicates that the performance of catalyst follows in the order of Ni>Co>Fe. The size

effect of catalyst particles would be an another factor to determine the growth rate of CNTs even though the growth rate mainly depend on the diffusion rate of carbons at the catalyst particles. The bamboo-like structured CNTs are exclusively produced irrespective to the catalyst. The CNTs grown on Fe catalyst reveals the best crystallinity among the three catalysts. On the other hand, the CNTs grown on Co catalyst exhibit much lower degree of crystalline character compared with Fe or Ni catalyst. We demonstrate that the growth rate, the diameter, and the crystallinity of CNTs can be manipulated by selecting the catalysts.

# 5. Acknowledgments

This work was supported by Institute of Information Technology Assessment

## 6. References

- [1] S. Iijima, Nature 354, (1991) 56.
- [2] C.-H. Kiang, J. Chem. Phys. 113, (2000) 4763.
- [3] A. N. Andriotis, M. Menon, G. Froudakis, Phys. Rev. Lett. 85, (2000) 3193.
- [4] Z. P. Huang, D. Z. Wang, J. G. Wen, M. Sennett, H. Gibson, Z. F. Ren, Appl. Phys. A 74, (2002) 387.
- [5] C. J. Lee, D. W. Kim, T. J. Lee, Y. C. Choi, Y. S. Park, W. S. Kim, Y. H. Lee, W. B. Choi, N. S. Lee, J. M. Kim, Y. G. Choi, S. C. Yu, Appl. Phys. Lett. 75, (1999) 1721.
- [6] C J. Lee, J. Park, Y. Huh, J. Y. Lee, Chem. Phys. Lett. 343, (2001) 33.
- [7] C. J. Smithells, Smithells' Metals Reference Book, 7<sup>th</sup> ed. Eds. E. A. Brandes and G. B. Brook, Butterworth-Heinemann Ltd., 1992.
- [8] C. Bower, O. Zhou, W. Zhu, D. J. Werder, S. Jin, Appl. Phys. Lett. 77, (2000) 2767.
- [9] C. J. Lee, J. Park, Appl. Phys. Lett. 77, (2000) 3397.
- [10] F. Tuinstra, J. L. Koenig, J. Chem. Phys. 53, (1970) 1126.