수직로 온도 분포 시뮬레이션

CFD Simulation of Temperature Distribution for the Vertical Furnace

<u>김성순</u>, 박성은*, 이홍림 연세대학교 세라믹공학과 *㈜ 새빛

수직로의 온도 제어는 로의 크기와 형상에 따라 다르지만 대부분의 경우 로 중심부에 설치한 하나의 열전대를 통해 이루어지게 된다. 즉 실험자가 신뢰할 수 있는 온도 영역은 열전대가 위치한 부분이며 그위치에서 조금이라도 벗어날 경우 시편이 열처리 과정 중에 겪게 되는 정확한 온도 이력을 알 수 없게된다 또한 분위기 소결시 내부 유입 기체에 따라 각 기체가 가지는 고유한 열역학적 특성 때문에 로 내의 온도분포가 변화하게 된다 수직로가 가지는 장점인 다양한 온도 영역을 실제 실험에 이용하고, 소결 온도의 신뢰성을 확보하기 위해서는 다양한 변수하에서 수직로의 온도분포에 대한 데이터의 확보가 절실히 요구된다

본 연구에서는 전산유체역학을 이용하여 발열부의 수, 내부 기체의 종류 및 유속에 따른 온도 분포 모델을 구축하였다 또한 시뮬레이션 모델의 신뢰성 확보를 위하여 실측 실험을 병행하였다 최종적으로 획득된 데이터와 시뮬레이션 모델과의 비교 분석을 통하여 모델의 검증을 하였다

P-166

Nanoscale Multilayers by Pulsed Vacuum Arc and Computer Simulation

Sung-Yong Chun Mokpo National University

A new technology for generating metal plasma using vacuum arc was developed to fabricate nano-scale metallic thin films and multilayers of a wide variety of materials. Nanoscale multilayers have been fabricated by pulsed vacuum arc with varying thickness of each layer from a few to tens of angstroms and examined by cross-sectional TEM Computer simulations were also performed for a better understanding of ballistic processes during the deposition