

## On Application of J-Q Theory for Different Specimen Geometries of Zr-2.5Nb Pressure Tube Material

Y.S. Kim, J.C. Park and H.C. Jeong, Yu. G. Matvienko,  
Korea Atomic Energy Research Institute,

### Abstract

The effect of specimen geometry on the fracture toughness of unirradiated and irradiated Zr-2.5Nb pressure tube material has been analyzed. The Q-parameter has been employed to characterize the geometry dependent crack-tip constraint of Zr-2.5Nb pressure tube material. The effect of specimen geometry on the crack-tip constraint parameter Q and the fracture toughness has been discussed. The fracture toughness scaling model has been developed to transfer standard CT fracture toughness data to burst test specimens.

---

## K-피복관의 부식특성 Corrosion Characteristics of K-Claddings

박정용, 최병권, 정용환, 정연호

한국원자력연구소

대전광역시 유성구 덕진동 150번지

### 요약

핵연료피복관의 부식저항성 개선은 고연소도 핵연료의 성공적인 개발을 결정하는 가장 중요한 요소이다. 한국원자력연구소는 합금원소의 첨가량을 조절하고 제조공정을 최적화하여 부식저항성이 월등히 개선된 신합금 핵연료피복관(K-피복관)을 개발하였다. 본 연구에서는 K-피복관 및 외국 피복관의 부식특성을 비교평가하고, 열처리에 따른 부식특성의 변화를 조사하였다. 부식시험은 360°C 순수물 분위기, 가압경수로의 냉각수조건을 모사한 loop 조건 및 400°C 수증기 분위기 등의 세가지 조건에서 수행되었다. 부식특성 평가 결과, K-피복관의 부식저항성이 Zry-4 및 A 피복관에 비하여 월등히 우수한 것으로 확인되었으며, K6 피복관의 부식저항성이 K3 피복관에 비하여 우수한 것으로 나타났다. K-피복관의 부식거동은 중간열처리보다는 최종열처리조건의 영향을 크게 받는 것으로 확인되었으며, 최종열처리온도가 감소할수록 부식저항성이 증가하였다.