


2005년 유체기계 연구개발 발표회 논문집
 Korean Fluid Machinery Association

Contents

- Backgrounds
- Objectives
- Physical Modeling Scale
 - Previous Studies
 - Selection of Model Scale
 - Test Criteria
- Measurement Apparatus
 - Configuration Test Facility
 - Pump Suction
- Model Test Results
 - Original Initial Test
 - Modified Remedial Test
- Conclusions



1 / 74

KOREAN FLUID MACHINERY ASSOCIATION

2005년 유체기계 연구개발 발표회 논문집
 Korean Fluid Machinery Association

오인 소하된 흡수용 SEA WATER INTAKE SYSTEM의 흡수조시험
 Sump Model Test on Sea Water Intake System
 for OJMW Scher Power and Desalination Project

- 2005년 유체기계연구개발회 유체기계 학술 대회 -

2005년 12월 1일(목) ~ 12월 2일(금)

서명수*, 김병수, 정기철, 박정식
 * E-MAIL: PABAK@K, EMAIL: YAS@HYUNDAI.COM

1 / 74

KOREAN FLUID MACHINERY ASSOCIATION

2005년 유체기계 연구개발 발표회 논문집
 Korean Fluid Machinery Association

Physical Modeling Scale

- Previous Literature & Study
 - ① Hecker, G.E.(1981)
 - ▶ Concluded Bouardian scaling gives reliable good results on proto & model
 - ① Anwar H.O(1978), Knauss, Josh(1978), ANS/HT(1998)
 - ▶ Suggested ψ orifice formation is independent of Radial Reynolds No."
 - ① The range of Weber no. is 50 ~ 75 that the vortex formation was unaffected as per experimental study by HR Wallingford
- Selection of Model Scale
 - ① Acquire dynamic similarity between prototype and model
 - ① Reproduce correctly vortex and swirl action at the pump suction
 - ① Impossible to satisfy simultaneously the scaling laws as follows
 - ▶ E = Euler number ; inertial force to pressure force
 - ▶ F = Froude number ; inertial force to gravitational force
 - ▶ R = Reynolds number ; inertial force to viscous force
 - ▶ W = Weber number ; inertial force to surface force

$$R_d = \frac{\rho V^2 D}{\mu} > 20,000 \sim 30,000$$

Radial Reynolds No.

$$W_e = \frac{4Q}{\pi D^2 \sigma} \sqrt{\rho \sigma}$$

Weber no.

1 / 74

KOREAN FLUID MACHINERY ASSOCIATION

2005년 유체기계 연구개발 발표회 논문집
 Korean Fluid Machinery Association

연구 배경

- ① 수리모형시험을 통한 펌프 운전상태의 예측 및 영향파의
- ① 펌프의 연속적이며 안정적인 운전실험을 위한 대책 수립
- ① 펌프의 부류 파손으로 인한 시간적 경제적 손실을 사전에 방지

연구 목적

- ① 불특수로 인한 소음, 진동발생에 대한 원인 규명
- ① 불특수의 관형(표면외류, 공기흡입외류, 수중외류)를 통한 펌프의 운전 상태 파악 및 방지 방안 수립
- ① 펌프장 흡입수조의 형상, 치수 설계 및 결점(HI Standard) 적합성 확인

1 / 74

KOREAN FLUID MACHINERY ASSOCIATION

Physical Model Scale

2005-2006 Korean High Technology Association

□ Test Criteria

① Calculation of model scale using Radial Reynolds No. and Weber No.

▶ Prototype information of sump

Q (m ³ /hr)	S (m)	D (m)	Remark
10,000	4	1.2	$\rho = 1000 \text{ kg/m}^3$, $\mu = 1.17 \times 10^{-3} \text{ Pa}\cdot\text{s}$, $\sigma = 0.0728 \text{ N/m}$

- ▶ Radial Reynolds no.: 7.5×10^5 , Weber no.: 930 for prototype
- ▶ $\lambda = 13$ (Radial Reynolds Number limit to 20,000)
- ▶ $\lambda = 19$ (Weber Number limit to 50)
- ▶ $\lambda = 10$; Experimental model scale by HECO

② Frouden Similarity between the model and prototype (HI/ISME)

$$F_r = \frac{V_m}{\sqrt{gL_m}} = \frac{V_p}{\sqrt{gL_p}}$$

$$V_m = V_p \left(\frac{L_m}{L_p} \right)^{1/2} \text{ or } Q_m = Q_p \left(\frac{L_m}{L_p} \right)^{3/2}$$

- ▶ $n = 0.5$; Same Froude
- ▶ $n = 0.2$; Medium Velocity
- ▶ $n = 0.0$; Equal Velocity

HYUNDAI ENGINE CO., LTD.

3/74

Radial Intake Vortex Test Set

Physical Inflow Scale


2005-2006 Korean High Technology Association

□ Test Criteria

① Scale ratios related with model test investigation

Parameter	HI	ISME 004 - 1984
Geometry (λ)	Froude No. 1:10	Equal Velocity 1:10
Velocity (V)	1:10 ^{0.5} = 1:3.16	1:10 ^{0.5} = 1:1
Flow Rate (Q)	1:10 ^{1.5} = 1:31.6	1:10 ^{1.5} = 1:100
Time (t)	1:10 ^{0.5} = 1:3.16	1:10
Swirl angle	5°	5°

② Measurement of swirl angle with vorticity meter



$$\theta = \tan^{-1} \frac{V_\theta}{V_z}; \text{ swirl angle}$$

- ▶ V_θ : Tangential velocity vector
- ▶ V_z : Axial mean velocity vector

HYUNDAI ENGINE CO., LTD.

8/74

Radial Intake Vortex Test Set

Physical Model Scale

2005-2006 Korean High Technology Association

□ Test Criteria

① Acceptance Criteria as per HI

▶ Prototype information of sump

Q (m ³ /hr)	S (m)	D (m)	Remark
10,000	4	1.2	$\rho = 1000 \text{ kg/m}^3$, $\mu = 1.17 \times 10^{-3} \text{ Pa}\cdot\text{s}$, $\sigma = 0.0728 \text{ N/m}$

- ▶ Radial Reynolds no.: 7.5×10^5 , Weber no.: 930 for prototype
- ▶ $\lambda = 13$ (Radial Reynolds Number limit to 20,000)
- ▶ $\lambda = 19$ (Weber Number limit to 50)
- ▶ $\lambda = 10$; Experimental model scale by HECO

② Frouden Similarity between the model and prototype (HI/ISME)

$$F_r = \frac{V_m}{\sqrt{gL_m}} = \frac{V_p}{\sqrt{gL_p}}$$

$$V_m = V_p \left(\frac{L_m}{L_p} \right)^{1/2} \text{ or } Q_m = Q_p \left(\frac{L_m}{L_p} \right)^{3/2}$$

- ▶ $n = 0.5$; Same Froude
- ▶ $n = 0.2$; Medium Velocity
- ▶ $n = 0.0$; Equal Velocity

HYUNDAI ENGINE CO., LTD.

3/74

Radial Intake Vortex Test Set

Physical Model Scale

2005-2006 Korean High Technology Association

□ Test Criteria

① Acceptance Criteria as per HI

Classification of Vortex	Acceptable Criteria
(1) Free Surface Vortices	
▶ Surface Swirl (Class A-1)	●
▶ Surface Dipplet (Class A-2)	●
▶ Dye Core (to Intake) (Class A-3)	×
(2) Sub Surface Vortices	
▶ Swirl (Class B-1)	●
▶ Dye core (Class B-2)	×
▶ Air Core or Bubbles	×
● Acceptable, × Not Acceptable	


HYUNDAI ENGINE CO., LTD.

1/74

Radial Intake Vortex Test Set


□ Configuration Test Facility

① General schematic layout of Onshore Intake Area for Pumping Station



□ Test Facility

① Configuration of Model Test Facility




HYDREUS ENGINE CO., LTD.

0/28

Recirculation Pump Sea Side

□ Test Facility

① Configuration of Model Test Facility (Continued)



Equipment	Specification	Maker	Remark
Magnetic Flow Meter(A)	Nominal Diameter : 250 A Accuracy : ± 0.3%	Bally Fisher & Porter	GERMANY
Magnetic Flow Meter(B)	Nominal Diameter : 150A Accuracy : ± 0.3%	HEINRICH	GERMANY
Magnetic Flow Meter(C)	Nominal Diameter : 150A Accuracy : ± 0.3%	ABB	SWEDEN
Magnetic Flow Meter(D)	Nominal Diameter : 80A Accuracy : ± 0.3%	YONGJAW A	JAPAN
Propeller Vortmeter	Installation flar Media : Water Fluid : Water	HYOJUNG-GBARD	KOREA


Measuring equipment

0/28

Recirculation Pump Sea Side

□ Test Facility

① Pump Suction and Swirl Meter



HYDREUS ENGINE CO., LTD.

0/28

Recirculation Pump Sea Side

□ Original Initial Test

① Case 1. Low Water Level (-1.5CD, 450mm)

■ case 1.1 Maximum flow rate (17,600 m³/hr)

▶ Equal velocity as per JSME

▶ Froude no. similarity as per HI

■ case 1.2 Rated flow rate (16,000 m³/hr)

▶ Equal velocity

▶ Froude no. similarity

② Case 2. Normal Water Level (-0.75CD, 635mm)

■ case 2.1 Maximum flow rate (17,600 m³/hr)


▶ Equal velocity as per JSME

▶ Froude no. similarity as per HI

■ case 2.2 Rated flow rate (16,000 m³/hr)

▶ Equal velocity

▶ Froude no. similarity



HYDREUS ENGINE CO., LTD.

0/28

Recirculation Pump Sea Side

Original Initial Test (Continued)

Case 2.1 Normal Water Level (+0.95CD, 495mm), Maximum flow rate

Test case	Pump Operation	Velocity	Water Level(mm)		Flow Rate(m ³ /hr)	Remark (Capacity)
			Prototype	Model		
02-M-W-1	A1-A2-A3	V	N.W.L (+0.95CD)	N.W.L (495)	17,600	176
02-M-W-2	A1-A2-A4	V	N.W.L (+0.95CD)	N.W.L (495)	17,600	176
02-M-W-3	A1-A3-A4	V	N.W.L (+0.95CD)	N.W.L (495)	17,600	176
02-M-W-4	A2-A3-A4	V	N.W.L (+0.95CD)	N.W.L (495)	17,600	176
02-M-F-1	A1-A2-A3	F	N.W.L (+0.95CD)	N.W.L (495)	17,600	36
02-M-F-2	A1-A2-A4	F	N.W.L (+0.95CD)	N.W.L (495)	17,600	36
02-M-F-3	A1-A3-A4	F	N.W.L (+0.95CD)	N.W.L (495)	17,600	36
02-M-F-4	A2-A3-A4	F	N.W.L (+0.95CD)	N.W.L (495)	17,600	36

Case 2.2 Normal Water Level (+0.95CD, 495mm), Rated flow rate

Test case	Pump Operation	Velocity	Water Level(mm)		Flow Rate(m ³ /hr)	Remark (Capacity)
			Prototype	Model		
03-R-W-1	A1-A2-A3	V	N.W.L (+0.95CD)	N.W.L (495)	16,000	160
03-R-W-2	A1-A2-A4	V	N.W.L (+0.95CD)	N.W.L (495)	16,000	160
03-R-W-3	A1-A3-A4	V	N.W.L (+0.95CD)	N.W.L (495)	16,000	160
03-R-W-4	A2-A3-A4	V	N.W.L (+0.95CD)	N.W.L (495)	16,000	160
03-R-F-1	A1-A2-A3	F	N.W.L (+0.95CD)	N.W.L (495)	16,000	51
03-R-F-2	A1-A2-A4	F	N.W.L (+0.95CD)	N.W.L (495)	16,000	51
03-R-F-3	A1-A3-A4	F	N.W.L (+0.95CD)	N.W.L (495)	16,000	51
03-R-F-4	A2-A3-A4	F	N.W.L (+0.95CD)	N.W.L (495)	16,000	51

HYUNDAI E&E CO., LTD. 8/74 Ball Institute Young Seo Lab

Original Initial Test

Case 1.1 Low Water Level (-1.5CD, 450mm), Maximum flow rate

Test case	Pump Operation	Similarity	Water Level(mm)		Flow Rate(m ³ /hr)	Remark (Capacity)
			Prototype	Model		
01-M-W-1	A1-A2-A3	Equal velocity	L.W.L (-1.5CD)	L.W.L (450)	17,600	176
01-M-W-2	A1-A2-A4	-	L.W.L (-1.5CD)	L.W.L (450)	17,600	176
01-M-W-3	A1-A3-A4	-	L.W.L (-1.5CD)	L.W.L (450)	17,600	176
01-M-W-4	A2-A3-A4	-	L.W.L (-1.5CD)	L.W.L (450)	17,600	176
01-M-F-1	A1-A2-A3	Froude no.	L.W.L (-1.5CD)	L.W.L (450)	17,600	56
01-M-F-2	A1-A2-A4	-	L.W.L (-1.5CD)	L.W.L (450)	17,600	56
01-M-F-3	A1-A3-A4	-	L.W.L (-1.5CD)	L.W.L (450)	17,600	56
01-M-F-4	A2-A3-A4	-	L.W.L (-1.5CD)	L.W.L (450)	17,600	56

Case 1.2 Low Water Level (-1.5CD, 450mm), Rated flow rate

Test case	Pump Operation	Similarity	Water Level(mm)		Flow Rate(m ³ /hr)	Remark (Capacity)
			Prototype	Model		
01-R-W-1	A1-A2-A3	Equal velocity	L.W.L (-1.5CD)	L.W.L (450)	16,000	160
01-R-W-2	A1-A2-A4	-	L.W.L (-1.5CD)	L.W.L (450)	16,000	160
01-R-W-3	A1-A3-A4	-	L.W.L (-1.5CD)	L.W.L (450)	16,000	160
01-R-W-4	A2-A3-A4	-	L.W.L (-1.5CD)	L.W.L (450)	16,000	160
01-R-F-1	A1-A2-A3	Froude no.	L.W.L (-1.5CD)	L.W.L (450)	16,000	51
01-R-F-2	A1-A2-A4	-	L.W.L (-1.5CD)	L.W.L (450)	16,000	51
01-R-F-3	A1-A3-A4	-	L.W.L (-1.5CD)	L.W.L (450)	16,000	51
01-R-F-4	A2-A3-A4	-	L.W.L (-1.5CD)	L.W.L (450)	16,000	51

HYUNDAI E&E CO., LTD. 8/74 Ball Institute Young Seo Lab

Original Initial Test Results

Case 1 Low Water Level (-1.5CD, 450mm), Maximum flow rate

Test Case	Pump Operation	Velocity	Water Level(mm)		Flow Rate(m ³ /hr)	Remark (Capacity)
			Prototype	Model		
01-M-W-1	A1-A2-A3	V	N.W.L (+0.95CD)	N.W.L (495)	17,600	176
01-M-W-2	A1-A2-A4	V	N.W.L (+0.95CD)	N.W.L (495)	17,600	176
01-M-W-3	A1-A3-A4	V	N.W.L (+0.95CD)	N.W.L (495)	17,600	176
01-M-W-4	A2-A3-A4	V	N.W.L (+0.95CD)	N.W.L (495)	17,600	176
01-M-F-1	A1-A2-A3	F	N.W.L (+0.95CD)	N.W.L (495)	17,600	36
01-M-F-2	A1-A2-A4	F	N.W.L (+0.95CD)	N.W.L (495)	17,600	36
01-M-F-3	A1-A3-A4	F	N.W.L (+0.95CD)	N.W.L (495)	17,600	36
01-M-F-4	A2-A3-A4	F	N.W.L (+0.95CD)	N.W.L (495)	17,600	36

Case 1 Low Water Level (-1.5CD, 450mm), Maximum flow rate

Test Case	Pump Operation	Velocity	Water Level(mm)		Flow Rate(m ³ /hr)	Remark (Capacity)
			Prototype	Model		
01-R-W-1	A1-A2-A3	V	N.W.L (+0.95CD)	N.W.L (495)	16,000	160
01-R-W-2	A1-A2-A4	V	N.W.L (+0.95CD)	N.W.L (495)	16,000	160
01-R-W-3	A1-A3-A4	V	N.W.L (+0.95CD)	N.W.L (495)	16,000	160
01-R-W-4	A2-A3-A4	V	N.W.L (+0.95CD)	N.W.L (495)	16,000	160
01-R-F-1	A1-A2-A3	F	N.W.L (+0.95CD)	N.W.L (495)	16,000	51
01-R-F-2	A1-A2-A4	F	N.W.L (+0.95CD)	N.W.L (495)	16,000	51
01-R-F-3	A1-A3-A4	F	N.W.L (+0.95CD)	N.W.L (495)	16,000	51
01-R-F-4	A2-A3-A4	F	N.W.L (+0.95CD)	N.W.L (495)	16,000	51

HYUNDAI E&E CO., LTD. 8/74 Ball Institute Young Seo Lab

Original Initial Test Results

Case 1 Low Water Level (-1.5CD, 450mm), Maximum & Rated flow rate


Test Case	Pump Operation	Velocity	Water Level(mm)		Flow Rate(m ³ /hr)	Remark (Capacity)
			Prototype	Model		
01-M-W-1	A1-A2-A3	V	N.W.L (+0.95CD)	N.W.L (495)	17,600	176
01-M-W-2	A1-A2-A4	V	N.W.L (+0.95CD)	N.W.L (495)	17,600	176
01-M-W-3	A1-A3-A4	V	N.W.L (+0.95CD)	N.W.L (495)	17,600	176
01-M-W-4	A2-A3-A4	V	N.W.L (+0.95CD)	N.W.L (495)	17,600	176
01-M-F-1	A1-A2-A3	F	N.W.L (+0.95CD)	N.W.L (495)	17,600	36
01-M-F-2	A1-A2-A4	F	N.W.L (+0.95CD)	N.W.L (495)	17,600	36
01-M-F-3	A1-A3-A4	F	N.W.L (+0.95CD)	N.W.L (495)	17,600	36
01-M-F-4	A2-A3-A4	F	N.W.L (+0.95CD)	N.W.L (495)	17,600	36

Case 1 Low Water Level (-1.5CD, 450mm), Maximum & Rated flow rate

Test Case	Pump Operation	Velocity	Water Level(mm)		Flow Rate(m ³ /hr)	Remark (Capacity)
			Prototype	Model		
01-R-W-1	A1-A2-A3	V	N.W.L (+0.95CD)	N.W.L (495)	16,000	160
01-R-W-2	A1-A2-A4	V	N.W.L (+0.95CD)	N.W.L (495)	16,000	160
01-R-W-3	A1-A3-A4	V	N.W.L (+0.95CD)	N.W.L (495)	16,000	160
01-R-W-4	A2-A3-A4	V	N.W.L (+0.95CD)	N.W.L (495)	16,000	160
01-R-F-1	A1-A2-A3	F	N.W.L (+0.95CD)	N.W.L (495)	16,000	51
01-R-F-2	A1-A2-A4	F	N.W.L (+0.95CD)	N.W.L (495)	16,000	51
01-R-F-3	A1-A3-A4	F	N.W.L (+0.95CD)	N.W.L (495)	16,000	51
01-R-F-4	A2-A3-A4	F	N.W.L (+0.95CD)	N.W.L (495)	16,000	51

HYUNDAI E&E CO., LTD. 8/74 Ball Institute Young Seo Lab

Original Initial Test Results



Case 1 Low Water Level (-1.5CD, 450mm), Maximum flow rate

Principle of Similarity	Capacity of SSP	Water Level
Same Froude No.	176m ³ /hr, Maximum flow capacity	LWL, 450mm (-1.5CD)
<ul style="list-style-type: none"> Submerged Vortex and Dipple; observed. SSP SEA operated CCWP, ASCP operated 		

HYUNDAI E&E CO., LTD. 8/74 Ball Institute Young Seo Lab

Original Initial Test Results

Case 1 Low Water Level (-1.5CD, 450mm), Maximum & Rated flow rate

Test Case	Pump Operation	Velocity	Water Level(mm)		Flow Rate(m ³ /hr)	Remark (Capacity)
			Prototype	Model		
01-M-W-1	A1-A2-A3	V	N.W.L (+0.95CD)	N.W.L (495)	17,600	176
01-M-W-2	A1-A2-A4	V	N.W.L (+0.95CD)	N.W.L (495)	17,600	176
01-M-W-3	A1-A3-A4	V	N.W.L (+0.95CD)	N.W.L (495)	17,600	176
01-M-W-4	A2-A3-A4	V	N.W.L (+0.95CD)	N.W.L (495)	17,600	176
01-M-F-1	A1-A2-A3	F	N.W.L (+0.95CD)	N.W.L (495)	17,600	36
01-M-F-2	A1-A2-A4	F	N.W.L (+0.95CD)	N.W.L (495)	17,600	36
01-M-F-3	A1-A3-A4	F	N.W.L (+0.95CD)	N.W.L (495)	17,600	36
01-M-F-4	A2-A3-A4	F	N.W.L (+0.95CD)	N.W.L (495)	17,600	36

Case 1 Low Water Level (-1.5CD, 450mm), Maximum & Rated flow rate





Test Case	Pump Operation	Velocity	Water Level(mm)		Flow Rate(m ³ /hr)	Remark (Capacity)
			Prototype	Model		
01-R-W-1	A1-A2-A3	V	N.W.L (+0.95CD)	N.W.L (495)	16,000	160
01-R-W-2	A1-A2-A4	V	N.W.L (+0.95CD)	N.W.L (495)	16,000	160
01-R-W-3	A1-A3-A4	V	N.W.L (+0.95CD)	N.W.L (495)	16,000	160
01-R-W-4	A2-A3-A4	V	N.W.L (+0.95CD)	N.W.L (495)	16,000	160
01-R-F-1	A1-A2-A3	F	N.W.L (+0.95CD)	N.W.L (495)	16,000	51
01-R-F-2	A1-A2-A4	F	N.W.L (+0.95CD)	N.W.L (495)	16,000	51
01-R-F-3	A1-A3-A4	F	N.W.L (+0.95CD)	N.W.L (495)	16,000	51
01-R-F-4	A2-A3-A4	F	N.W.L (+0.95CD)	N.W.L (495)	16,000	51

HYUNDAI E&E CO., LTD. 8/74 Ball Institute Young Seo Lab

2008년 10월 17일 17:00분 현재
Korea Fluid Machinery Association

Original Initial Test Results

① Case 1 Low Water Level (-1.5CD, 450mm), Maximum flow rate

		Principle of Similarity	Some Froude No.
		Capacity of SSP	176m ³ /hr, Maximum flow capacity
		Water Level	LWL, 450mm (-1.5CD)
<input type="checkbox"/> Submerged vortex and Dimple observed. <input type="checkbox"/> SSP 3EA operated <input type="checkbox"/> CCWP, ASCP operated			

D / 7%





Korea Fluid Machinery Association

HYSUNG E&E CO., LTD.

2008년 10월 17일 17:00분 현재
Korea Fluid Machinery Association

Original Initial Test Results

② Case 1 Low Water Level (-1.5CD, 450mm), Rated flow rate

		Principle of Similarity	Equal Velocity
		Capacity of SSP	160m ³ /hr, Maximum flow capacity
		Water Level	LWL, 450mm (-1.5CD)
<input type="checkbox"/> Submerged vortex and Dimple observed. <input type="checkbox"/> SSP 3EA operated <input type="checkbox"/> CCWP, ASCP operated			

R / 7%





Korea Fluid Machinery Association

HYSUNG E&E CO., LTD.

2008년 10월 17일 17:00분 현재
Korea Fluid Machinery Association

Original Initial Test Results

① Case 1 Low Water Level (-1.5CD, 450mm), Maximum flow rate

		Principle of Similarity	Equal Velocity
		Capacity of SSP	176m ³ /hr, Maximum flow capacity
		Water Level	LWL, 450mm (-1.5CD)
<input type="checkbox"/> Submerged vortex and Dimple observed. <input type="checkbox"/> SSP 3EA operated <input type="checkbox"/> CCWP, ASCP operated			

D / 7%





Korea Fluid Machinery Association

HYSUNG E&E CO., LTD.

2008년 10월 17일 17:00분 현재
Korea Fluid Machinery Association

Original Initial Test Results

② Case 1 Low Water Level (-1.5CD, 450mm), Rated flow rate

		Principle of Similarity	Same Froude
		Capacity of SSP	160m ³ /hr, Maximum flow capacity
		Water Level	LWL, 450mm (-1.5CD)
<input type="checkbox"/> Submerged vortex and Dimple observed. <input type="checkbox"/> SSP 3EA operated <input type="checkbox"/> CCWP, ASCP operated			

R / 7%


Korea Fluid Machinery Association

HYSUNG E&E CO., LTD.

Model Test Results

☐ Modified Remedial Test Results

① Case 1 Low Water Level (-1.5CD, 450mm). Rated flow rate



HYUNDAI E&E CO., LTD. 27/74

Multi-layers Vortex flow test box

Model Test Results

☐ Modified Remedial Test

① Anti-Vortex Device and Curtain Wall



Water Level	Flow Rate [m ³ /hr]	Anti-Vortex Device		Similarity	Remark
		L-Splitter	Wall Curtain		
-1.5CD	17,600/56	●	X	Same Froude No.	Distribution Baffle
-0.72CD	17,600/56	●	X	Same Froude No.	Distribution Baffle

HYUNDAI E&E CO., LTD. 27/74

Multi-layers Vortex flow test box

Model Test Results

☐ Modified Remedial Test

① Installation of Anti-Vortex Device and Curtain Wall

Test Case	Type of Vortex Formation											
	BSP-A	BSP-B	BSP-C	BSP-D	ABCP	BSP-A	BSP-B	BSP-C	BSP-D	CCWP	ACCP	
Maximum Flow rate	Q1-MV-1	R	R	R	R	R	R	R	R	R	R	R
	Q1-MV-2	R	R	R	R	R	R	R	R	R	R	R
	Q1-MV-3	R	R	R	R	R	R	R	R	R	R	R
	Q1-MV-4	R	R	R	R	R	R	R	R	R	R	R
Rated flow rate	Q1-ME-1	R	R	R	R	R	R	R	R	R	R	R
	Q1-ME-2	R	R	R	R	R	R	R	R	R	R	R
	Q1-ME-3	R	R	R	R	R	R	R	R	R	R	R
	Q1-ME-4	R	R	R	R	R	R	R	R	R	R	R
	Q1-RV-1	R	R	R	R	R	R	R	R	R	R	R
	Q1-RV-2	R	R	R	R	R	R	R	R	R	R	R
	Q1-RV-3	R	R	R	R	R	R	R	R	R	R	R
	Q1-RV-4	R	R	R	R	R	R	R	R	R	R	R
Rated flow rate	Q1-RE-1	R	R	R	R	R	R	R	R	R	R	R
	Q1-RE-2	R	R	R	R	R	R	R	R	R	R	R
	Q1-RE-3	R	R	R	R	R	R	R	R	R	R	R
	Q1-RE-4	R	R	R	R	R	R	R	R	R	R	R

HYUNDAI E&E CO., LTD. 27/74

Multi-layers Vortex flow test box

①: A geometry model of the pumping station was constructed at a scale of 1:13 and tests were undertaken to investigate;

- ▣ Flow conditions at the screen chambers
- ▣ Approaching flow conditions to the pump chambers and suction
- ▣ Ensure that the entering flow to pump suction was free from severe swirl
- ▣ Ensure that the pump chambers were free from severe vortex action and no air was entrained at the pump suction
- ▣ Identify modifications of baffles and anti-vortex device to improve the pump operation performance

②: The results of original model test are ;

- ▣ Submerged vortex developed in the pump chamber was not within acceptable criteria
- ▣ Air-entraining vortex in the pump chamber surface was not within acceptable criteria
- ▣ Pre-swirl occurred at the pump suction was not within allowable swirl angle, 5°

감사합니다!

④: Modified remedial test results with anti-vortex device to eliminate submerged vortices with pre-swirl flow are ;

- ▣ No submerged vortex was observed from the side and bottom wall
- ▣ Pre-swirl angle at the inlet of pump suction was within acceptable limit

⑤: Modified remedial test demonstrated the effectiveness of splitter device was in effective of elimination of sub-vortex and swirl at the pump suction "