한국소음진동공학회 2005년도 춘계학술대회논문집, pp.231~231.

초소형 광디스크 드라이브의 충격절연장치 설계

The design of shock isolator for small form factor optical disk drives

장영배*·김시정**·박노철***·박영필**** Young-Bae Chang, Shi-Jung Kim, No-Cheol Park and Young-Pil Park

Key Words: Small Form Factor Optical Disk Drive(초소형광디스크드라이브), Finite Element Model(유한요소모델), Shock Response(충격응답), Shock Isolator Design(충격절연장치설계)

ABSTRACT

Because digital and mobile devices such as PDA and mp3 player are widely used, small-sized information storage devices are needed, which supports the storage part of these devices. The small form factor optical disk drive is a strong candidate of leading storage devices. But the small form factor optical disk drive is weak in external shock. When the drive is subjected to the external shock, the pickup will crashes on the disk surface, and it can cause the damage on the pickup assembly and disk. In this research, a finite element model of small form factor optical disk drive. A finite element model is made by using conventional finite element analysis tool, Ansys/Ls-Dyna. Shock responses are obtained using this finite element model according to various shock acceleration. And the design method of shock isolator is suggested in order to reduce the shock response of small form factor optical disk drive exposed shock environment. Small form factor optical disk drive can be modeled as a 2 DOF system. This 2 DOF model can help us to analyze the influence of absorber parameters on SFF ODD, systematically. Through the studies of the shock response in 2 DOF model, the optimal parameters of the shock isolator can be presented. Last, it is shown that adjusting the natural frequency ratio of bumper can improve the shock characteristics in finite element model.

후 기

본 연구는 한국과학재단 지정 정보저장기기 연구 센터[CISD] (R11-1997-042-11000-0)의 지원을 받 아 이루어졌으며, 이에 관계자 여러분께 감사 드 립니다.

^{*} 연세대학교 기계공학과 대학원 E-mail: gorio015@cisd.yonsei.ac.kr Tel: (02) 2123-4677, Fax: (02) 365-8460

^{**} 삼성전자 스토리리 사업부

^{***} 연세대학교 정보저장협동과정

^{****} 연세대학교 기계공학과