Densification Behaviors of Fe-Tic System during Spark Plasma Sintering

Yong-Hee Lee¹*, Dong-Kyu Park¹, Sung-Yeal Bae², In-Sup Ahn²

¹Kaya AMA Inc. 1010-1, Baerok, Habuk, Yangsan, Gyeongnam, 626-862, Korea ²Gyeongsang National univ. 900, Gawza, Jinju, Gyungnam, 660-701, Korea

Abstract

The SPS process is a synthetic technique which makes sinter-bonding possible at a lower temperature in a shorter sintering time and then becomes finer grain size than conventional sintering methods.

Fe-TiC system is relatively light material one third of tungsten carbide and less than a half of tool steel in weight. And then it gives reasonable price of Fe-TiC system due to high mass effect with low density and relatively low cost of changing tools and bearings etc. Fe-TiC system can be machined easily by conventional equipment.

In the present work, SPS was conducted in the temperature range from 1000° C to 1150° C for 10min at constant heating rate and pressure. And then, physical properties and grain size after sintering were evaluated at various Fe contents.

PB06-T-14

Sintering of MA956 Powder by SPS and Strengthening by Addition of W and Mo

Chunfeng Tang¹, Xuanhui Qu², Ting Zhou², Lei Li²

¹P/M Institute, University of Central South,P.R.China; ²Department of Material Science and Engineering, University of Science and technology Beijing, P.R.China

Abstract

The sintering way of SPS and effect of W and Mo on the properties of MA956 was investigated. The powders become amorphous and grain size is less than 40 nm after MA in a planetary milling machine for 48h with a milling rate of 280r/min. When SPS sintering temperature is above 900°C, sintered compact density is above 99.1% and nearly full. And the alloy grain size is below 0.7um. The addition of 3%wt W/Mo can increase pressure strength of room and 800°C, but its ductility decrease somewhat. Element W is better than Mo in improvement of high temperature relaxation behavior.