

# Structure and mechanical characteristics of TiZrAlN nanostructured thin films by CFUBMS

Youn J. Kim, Ho Y. Lee, Yong M. Kim\*, Jeon G. Han

Department of Advanced Materials Engineering, SungKyunKwan University Suwon 440-746, Korea

\*Center for Advanced Plasma Surface Technology, SungKyunKwan University Suwon 440-746, Korea

Industries such as the tool and forming industries are keenly interested in increasing the lifetimes of their components. This is a motivation for the choice of nitride coatings, which have been selected because of their mechanical properties such as hardness as well as wear resistance. Of the various coatings, titanium nitride has become an established industrial coating that is most commonly used in the tool industry [1]. However, TiN films are restricted to application of high speed tool industry due to their low hardness of  $\sim 20$  GPa [2, 3]. Therefore, nanostructured coating materials have recently attracted increasing interest due to the unique properties, such as superhardness ( $H > 40$  GPa), combined high hardness and toughness, or high hardness and low friction [4].

In this study, the quaternary TiZrAlN nanostructured films are synthesized by Closed Field Unbalanced Magnetron Sputtering (CFUBMS) and the relationship of their microstructure and mechanical properties is investigated at various  $N_2$  partial pressures.

Grain refinement of TiZrAlN nanostructured thin film is occurred by controlling  $N_2$  partial pressure. Maximum hardness value according to the various  $N_2$  partial pressures is approximately 47 GPa. It is also conformed that critical value of the grain size  $d_c$  needs to achieve the maximum hardness.

## [참고문헌]

1. K. Holmberg, A. Matthews, Coatings Tribology, Tribology Series, vol. 28, Elsevier, Amsterdam, 1994.
2. O. Knotek, M. Bohmer, T. Leyendecker, J. Vac. Sci. Technol., A 4 (1986) 2695.
3. W. D. Munz, J. Vac. Sci. Technol., A 4 (1986) 2717.
4. C. Mitterer et al. Surf. Coat. Technol. 120/121 (1999) 405-411.