

BB03

Collective Magnetic Behavior in Surface-supported Nanodot Assemblies

J. Shen^{1,2,3}

¹Materials Science and Technology Division, Oak Ridge National Laboratory, Oak Ridge, TN 37831

²Center for Nanophase Materials Science, Oak Ridge National Laboratory, Oak Ridge, TN 37831

³Dept. of Phys. and Astronomy, The University of Tennessee, TN 37996

In this talk, I will discuss several novel methods for synthesizing surface-supported magnetic nanodot assemblies. I will then report collective ferromagnetic behavior in two-dimensional Fe dot assemblies on the Cu(111) surface that persists above room temperature. Our ability to tune the average size and spacing of the dots enables us to investigate the relative contributions of the mechanisms that support this unexpectedly robust magnetic order. Our experimental results and simulations indicate that the high-Tc ferromagnetism cannot be explained by either magnetic anisotropy or the simple dipolar interaction. Therefore, the ferromagnetic order in the Fe dot assemblies is a result of an indirect exchange interaction via the Cu(111) substrate. New experimental evidence indicates that the indirect exchange interaction is mediated by the surface electronic states on Cu(111).

REFERENCES

[1] M.A. Torjia, A.P. Li, X. C. Guan, E.W. Plummer, and J. Shen, *Phys. Rev. Lett.* **95**, 257203 (2005).
 [2] M.A. Torjia, Z. Gai, N. Myoung, E.W. Plummer, and J. Shen, *Phys. Rev. Lett.* **95**, 27201 (2005).
 [3] Zheng Cai, J.Y. Howe, Jiaodong Guo, D.A. Blom, E.W. Plummer, and J. Shen, *Appl. Phys. Lett.* **86**, 023107 (2005).
 [4] J. P. Pierce, M.A. Torjia, Z. Gai, Junren Shi, T.C. Schulthess, G.A. Farnan, J. F. Wendelken, E.W. Plummer, and J. Shen, *Phys. Rev. Lett.* **92**, 237201 (2004).
 [5] Zheng Cai, Biao Wu, J. P. Pierce, G.A. Farnan, D.J. Shu, M. Wang, Zhenyu Zhang, and J. Shen, *Phys. Rev. Lett.* **89**, 235502 (2002).

BBO4

Thermal and transport properties of a single nickel nanowire

M. N. Ou^{1,2}, **S. R. Harutyunyan**^{1,3}, **S. J. Lai**¹, **C. D. Chen**¹, **T. J. Yang**² and **Y. Y. Chen**¹

¹Institute of Physics, Academia Sinica, Taipei, Taiwan, ROC

²Department of Electrophysics, National Chiao Tung University, Hsinchu, Taiwan, ROC

³Institute for Physical Research, N.A.S.Ashtarak-2, Armenia

*Corresponding author: oumn@phys.sinica.edu.tw, Phone: +886 2 2788 0058 Ext.1017, Fax: +886 2 2783 4187

The thermal conductivity (κ), specific heat (C_p) and the resistivity (ρ) of a single nickel nanowire have been measured in the temperature range from 4 to 300 K by means of the "self heating 3ω " technique. Starting with a 100 nm nickel film grown on a Si3N4/Si substrate by thermal evaporation, a suspended nickel nanowire was then fabricated through e-beam lithography and etching processes. The width and length of the wire were determined by scanning electron microscope (SEM) as 180 nm and 35 μm re-spectively. At 300 K the thermal conductivity of nanowire is $\sim 20\%$ of the bulk, it diminishes to lower value as temperature decreases. The consequence is opposite to that of the bulk and might be explained by the restriction of mean free paths of electron/phonon-phonon interactions due to the grain boundaries. An enhancement of specific heat $\sim 200\%$ of the bulk is also observed. In addition, the resistivity of nanowire at room temperature is about four times larger than that of the bulk. The small relative resistivity ratio (RRR) confirms the polycrystalline characteristic of the nanowire. The magnetic field dependence of $\kappa(T)$, $C(T)$, and $\rho(T)$ will also be discussed.