

Fabrication and Microstructure Characterization of Fibrous Porous SiC-Si₃N₄/AlN composite Using Multi-pass Extrusion process

Shamiul Islam, Rajat Kanti Paul*, Hee-Dong Jang**, Byong-Taek Lee*,†

Department of Display Materials Engineering, Soonchunhyang University;

*Department of Biomedical Engineering and Materials;

**Korean Institute of Geoscience & Mineral Resources (KIGAM), Deajeon 305-350, South Korea
(lbt@sch.ac.kr†)

A laminated microstructure of fibrous porous SiC-Si₃N₄/AlN composite was fabricated using multi-pass extrusion process. In the 2nd and 3rd passed samples, the diameter of AlN fibers in the SiC-Si₃N₄ matrix was found to be 250 μm and 35 μm, respectively. AlN fibers were refined with the increase of extrusion pass number. The mechanical properties of SiC-Si₃N₄/AlN composite were compared with those of constituent SiC-Si₃N₄ and AlN layers. The detailed microstructure and phase analysis were investigated using OM, SEM, XRD techniques.

Keywords: Multi-pass extrusion process, SiC-Si₃N₄/AlN composite, microstructure, mechanical properties

IN VITRO MODEL OF BIOACTIVE BI-STRUCTURED CERAMIC-POLYMER NANOHYBRIDS

K.-Y. Lee, H.-J. Choi†

School of Advanced Materials Engineering, Yonsei University

(hjc@yonsei.ac.kr†)

Synthetic model of a large crack-free monolithic ceramic-polymer hybrid, which was synthesized using triethoxysilane end-capped poly (tetramethylene oxide) (Si-PTMO) modified tetra-ethoxysilane (TEOS)-PTMO bulk, was examined in the CaO-SiO₂-PTMO sol-gel system. Bulk precursor with nominal mass ratio of PTMO: TEOS = 80: 20 and surface precursor with nominal molar ratio of TEOS: Ca(NO₃)₂ = 1: 0.3 were subjected to hybrid-ization through hydrolysis and condensation process, producing a bi-structured hybrid, in which poly-meric bulk was molecular hybridized with bioactive silicate surface. Spectroscopic and microscopic characterizations revealed that the surface of hybrid was typical bioactive silicate. In vitro study using a simulated body fluid (SBF) revealed that the hybrid formed an osteo-inductive apatite on its surface within only 6 hours, suggesting bioactive materials with high capability of tissue integration as well as polymeric physical properties.

Keywords: bioactive, bi-structured, hybrid