

EQ04

**Study of Discontinuous FeCoSi/ Native-oxide Multilayer Films Operating in Gigahertz Frequency Range**

Huaping Zuo, Shihui Ge\*, Zhenkun Wang, Yuhua Xiao, and Dongsheng Yao

Key Laboratory for Magnetism and Magnetic Materials of Ministry of Education, Lanzhou University, Lanzhou, P.R.China

\*Corresponding author: e-mail: gesh@lzu.edu.cn

Two important parameters of soft magnetic materials required for high frequency applications are permeability and ferromagnetic resonance (FMR) frequency. For a magnetic film with in-plane uniaxial anisotropy field  $H_k$  and saturation magnetization  $4\pi M_s$ , the initial permeability  $\mu_i$  (the real part of the complex permeability  $\mu = \mu' - j\mu''$  at zero frequency) and resonance frequency  $f_r$  are given by

$$\mu_i = 1 + \frac{4\pi M_s^2}{H_k} \quad (1)$$

$$f_r = \frac{\gamma}{2\pi} \sqrt{4\pi M_s \times H_k} \quad (2)$$

where  $\gamma$  is the gyromagnetic factor. Equations (1) and (2) reveal an inherent tradeoff, known as the Snoek limit [1], between initial permeability and ferromagnetic resonance frequency. Therefore, the ability to easily optimize  $\mu_i$  and  $f_r$  for the high frequency application of soft magnetic thin film is desirable.

In this work, discontinuous [FeCoSi (d)/native-oxide]<sub>50</sub> multilayer films with tunable  $H_k$  and  $4\pi M_s$  were prepared by DC magnetron sputtering without using gradient sputtering method or any postfabrication treatment. The results reveal that  $H_k$  and  $4\pi M_s$  of the films increase simultaneously as magnetic FeCoSi layer thickness  $d$  was increased from 5.5 to 20.5 Å. As a consequence, as shown in Fig. 1, the resonance frequencies  $f_r$  of the films continuously increased from 2.0 to almost 4.0 GHz. Furthermore, the large  $\mu_i$  above 100 for all films was achieved due to the large and increasing  $4\pi M_s$  as  $d$  was increased. The combination of these properties makes the [FeCoSi (d)/native-oxide]<sub>50</sub> films potential candidates for high frequency magnetic devices.




Fig. 1. The initial permeability  $\mu_i$  and resonance frequency  $f_r$  for the samples at various magnetic FeCoSi thicknesses  $d$ .

REFERENCES

[1] J. L. Snoek, Physica 14, 207 (1948).

EQ05

**Researching Arsenic Absorbability of Magnetic Nanoparticles Fe<sub>3</sub>O<sub>4</sub> Coated with Oleic and Alginic Coatings**

Le Khanh Vinh<sup>1</sup>, Tran Hoang Hai<sup>1</sup>, Le Hong Phuc<sup>1</sup>, Doan Thi Kim Dung<sup>1</sup>, Bui Duc Long<sup>1</sup>, and Ly Thi My Huong<sup>2</sup>

<sup>1</sup>Ho Chi Minh Institute of Physics

<sup>2</sup>Can Tho University

Arsenic species are toxic compounds which present widely in water source in many countries, especially in Vietnam. Environmental health problems related to industrial waste streams and related drinking water contaminations can commonly occur. Removing or decreasing arsenic contaminations level effectively (according to WHO standards) is current facing many difficulties in technologies. This work focused on synthesizing magnetic nanoparticles with sodium oleate and alginate coatings in order to investigating whether or not effectiveness of arsenic removal can be increased by oleate and alginate coated magnetic nanoparticles. Magnetite nanoparticles were synthesized by co-precipitation method from FeCl<sub>2</sub> and FeCl<sub>3</sub> solution, coated by sodium oleate and alginate. Phase structure of these particles was determined by XRD, morphology were observed by TEM, SEM, and magnetic behaviors of these superparamagnetic nanoparticles were analyzed by hysteresis loop of VSM. Removal process were proceed with alter magnetic field by separation technique. Detection of arsenic was investigated using various types of electrodes, electrolytes.