

[ID-10] Design of CQUEAN (CCD Camera for QUasar in Early uNivers)

Eunbin Kim¹, Heeyoung Oh¹, Huynh Anh Le Nguyen¹, Soojong Pak¹, and Myungshin Im²

¹*Department of Astronomy and Space and Science, Kyung Hee University,* ²*Center for the Exploration of the Origin of the Universe (CEOU), Department of Physics and Astronomy, Seoul National University*

We are developing CCD camera, CQUEAN (Camera for QUasar in Early uNivers), that can detect Y-band ($\lambda=1.005\mu\text{m}$) for observing quasars at $z > 7$ in the early universe. The detector consists of two HPK $2k \times 4k$ CCD with a pixel size of $15 \mu\text{m}$. The thick back illuminated CCD is fabricated on high resistivity silicon. The advantages of the device are its thicker depletion layer, which improves the QE(40% at Y-band) and the absence of interference fringing. The camera will be placed on the McDonald 2.1m telescope (Otto Struve telescope) of the University of Texas at Austin. With the telescope diameter of 2.08m (82inch) and F/13.7, the pixel scale will be 0.11 arcsec/pix and the CCD FOV is 7.4×7.4 arcmin. In this presentation, we will show the conceptual design for CQUEAN and thermal analysis for the cryostat. We will use controller electronics from ARS, Astronomical Research Camera, Inc., and the control software will be developed on the Linux platform. We plan to see the first light by the end of 2010.

[ID-12] Development of tantalum based superconducting tunnel junctions

Ho Seop Yoon^{1,2,3}, Young-Sik Park², Jang-Hyun Park², Min Kyu Yang³, Jeon Kook Lee³, Yonuk Chong⁴, Yong-Ho Lee⁴, Sang-Kil Lee⁴, Dong-Lak Kim⁵, and Sug-Whan Kim¹

¹*GSOL, Dept. of Astronomy of Space Science, Yonsei University,* ²*Korea Astronomy and Space Science Institute(KASI),* ³*Korea Institute of Science and Technology(KIST),* ⁴*Korea Research Institute of Standards and Science(KRIS),* ⁵*Korea Basic Science Institute(KBSI)*

We report the successful fabrication and I-V curve superconductivity test results of the Ta-based superconducting tunnel junctions(STJ). STJ device is a candidate detector for next-generation astronomy. Because it is capable of counting photons from X-ray to NIR while exhibiting a high quantum efficiency, a high temporal response and an energy resolution much better than that of semiconductor-based devices. STJ with side-lengths of 20, 40, 60 and 80 μm were fabricated by deposition of Ta/Al/AlOx/Al/Ta 5-layer thin films incorporated on a 2-inch silicon wafer. These STJ thin-films were fabricated using UV

photo-lithography, DC magnetron sputtering, reactive ion etching(RIE), and chemical vapor deposition(CVD) techniques. I-V curve superconducting state test for STJ was succeeded in 4K with liquid helium cooling system. Their performance indicators such as energy gap, normal resistance, normal resistivity, dynamic resistance, dynamic resistivity, and quality factor were measured from I-V curve. The STJ material analysis results obtained from x-ray diffraction(XRD) and scanning electron microscope(SEM) are also presented.

[ID-13] Ultra Fast Flash Observatory to observe the prompt photons from Gamma Ray Bursts

Jiwoo Nam¹, Steven Boggs², G. Ripov³, Bruce Grossan², Jin-A Jeon¹, Joo-Young Jin⁴, Ae-Ra Jung¹, Ji-Eun Kim¹, Minsoo Kim⁴, Yong-Kweon Kim⁴, P. Klimov³, B. Khrenov³, Chang-hwan Lee⁵, Jik Lee¹, Go-Woon Na¹, Shin-Woo Nam¹, Il-Heung Park¹, Jae-Hyoung Park¹, Yong-Sun Park⁶, G. F. Smoot⁷, Jung-Eun Suh¹, Byoung-Wook Yoo⁴

¹*Department of Physics and Research Center for MEMS Space Telescope, Ewha Womans University,* ²*SSL, University of California at Berkeley,* ³*D. V. Skobeltsyn Institute of Nuclear Physics of Moscow State University,* ⁴*School of Electrical Engineering and Computer Science, Seoul National University,* ⁵*Department of Physics, Pusan National University,* ⁶*School of Physics and Astronomy, Seoul National University,* ⁷*BCCP, University of California at Berkeley*

UFFO (Ultra Fast Flash Observatory) is an ultra-fast optical/UV telescope which can slew to targets within 1 msec using MEMS (Micro-Electro-Mechanical Systems) micromirrors. It is utilized for observations of prompt optical/UV photons from GRBs (Gamma Ray Bursts), permitting the first ever systematic study of optical/UV emission far earlier than 1 sec after trigger. Topics of interest include short vs. long GRB prompt emission, which may have different emission time scales and mechanisms, and potential prompt emission from otherwise "dark" GRBs. We describe a concept and optical designs of the UFFO, and report lap-test results using a prototype telescope

[ID-14] Development of a Correlation Tracker System for New Solar Telescope: Software

Seonghwan Choi^{1,2}, Jakyoun Nah¹, Yong-Jae Moon², and Young-Deuk Park¹

¹*Korea Astronomy and Space Science Institute (KASI),* ²*Department of Astronomy and Space science, Kyunghee University*