

SW-P008

### Low Temperature Dissociation of SiOx by Gold

이정재<sup>1</sup>, 양미현<sup>2,3</sup>, 쿠마르 요계쉬<sup>3\*</sup>, 임규욱<sup>3</sup>, 강태희<sup>3</sup>, 정석민<sup>1</sup>

<sup>1</sup>포항공과대학교, <sup>2</sup>성균관대학교, <sup>3</sup>포항가속기연구소

The native silicon-oxide (SiO<sub>x</sub>) layer at the metal/Silicon interface acts as an electrical resistance to the metal contact of devices. Various methods are proposed for removing this layer, such as sputtering before metal contact formation or high temperature annealing. We studied the chemical evolution of the Au/SiO<sub>x</sub>/Si system during the annealing at 500°C using a spatially resolved photoelectron emission method. Scanning photoelectron emission microscopy (SPEM) and core level spectra from local area of the sample show the inhomogeneous oxidation and formation of silicide of Au, as well as valence band spectra reveals the role of Au atoms during the dissociation process of SiO<sub>x</sub>.

**Keywords:** native silicon-oxide, gold, Scanning photoelectron emission microscopy (SPEM), annealing

SW-P009

### Support Effect of Catalytic Activity on 3-dimensional Au/Metal Oxide Nanocatalysts Synthesized by Arc Plasma Deposition

Chan Ho Jung<sup>1</sup>, B. Naik<sup>1</sup>, Sang Hoon Kim<sup>2</sup>, and Jeong Y. Park<sup>1\*</sup>

<sup>1</sup>Graduate School of EEWS (WCU) and Nanocentury KI, KAIST, Daejeon, 305-701, Korea,

<sup>2</sup>Interfacial Engineering Center, KIST, Seoul, 136-791, Korea

Strong metal-support interaction effect is an important issue in determining the catalytic activity for heterogeneous catalysis. In this work, we report the catalytic activity of Au/TiO<sub>2</sub>, Au/Al<sub>2</sub>O<sub>3</sub>, and Au/Al<sub>2</sub>O<sub>3</sub>-CeO<sub>2</sub> nanocatalysts under CO oxidation fabricated by arc plasma deposition (APD), which is a facile dry process with no organic materials involved. These catalytic materials were characterized by transmission electron microscopy (TEM), energy-dispersive X-ray spectroscopy (EDS) and N<sub>2</sub>-physisorption. Catalytic activity of the materials has measured by CO oxidation using oxygen, as a model reaction, in a micro-flow reactor at atmospheric pressure. Using APD, the catalyst nanoparticles were well dispersed on metal oxide powder with an average particle size (3~10 nm). As for catalytic reactivity, the result shows Au/Al<sub>2</sub>O<sub>3</sub>-CeO<sub>2</sub> nanocatalyst has the highest catalytic activity among three samples in CO oxidation, and Au/TiO<sub>2</sub>, and Au/Al<sub>2</sub>O<sub>3</sub> in sequence. We discuss the effects of structure and metal-oxide interactions of the catalysts on catalytic activity.

**Keywords:** arc plasma deposition, CO oxidation, support effect