

TW-P025

## Enhanced Performance in Isoindigo Based Organic Small Molecules Field Effect Transistors Using Solvent Additives

박유정<sup>1</sup>, 조신욱<sup>2</sup>, 서정화<sup>3\*</sup>

Department of Materials Physics, Dong-A University, <sup>1</sup>Department of Materials Physics and EHSRC, University of Ulsan, <sup>2</sup>Department of Materials Physics, <sup>3</sup>Dong-A University

Isoindigo based small molecules have attracted much attention in the field of optoelectronic devices due to their broad absorbance and high charge carrier mobilities. Herein, we investigate the field effect transistor characteristics of a series of isoindigo based donor-acceptor-donor (D-A-D) small molecules containing a variable number of thiophene moieties (named IDT, ID2T, and ID3T) which form pi-bridges between the D and A moieties and a different donor moiety (IDED). In order to improve the carrier mobility, 1-chloronaphthalene (CN) and 1,8-diodooctane (DIO) as solvent additives were used. The film morphology, crystallinity and optical properties of the materials processed with various concentrations of solvent additives were investigated through atomic force microscopy (AFM), X-ray diffraction (XRD) and UV-vis absorption spectroscopy.

**Keywords:** isoindigo, additive

TW-P026

## Structural Characteristics of Spray-coated Poly (vinylidene fluoride) Thin Films Prepared with Different Organic Solvents

정낙천<sup>1</sup>, 임영택<sup>1</sup>, 이선우<sup>2</sup>, 신백균<sup>1</sup>

<sup>1</sup>인하대학교 전기공학과, <sup>2</sup>인하공업전문대학 전기정보과

Poly (vinylidene fluoride) thin films were deposited by a spray-coating technology. Two organic solvents with different boiling point were used to prepare the mixture solution for spray coating process: N-Methylpyrrolodone (B.P.=202°C); Tetrahydrofuran (B.P.=66°C). Post-deposition annealing temperature was varied for the spray-coated Poly(vinylidene fluoride) thin films. Structural characteristics of the thin films were comparatively investigated by FT-IR and XRD in relation with the organic solvent and post-deposition annealing temperature.

**Keywords:** Poly (vinylidene fluoride), spray-coating, N-Methylpyrrolodone, Tetrahydrofuran