Effect of an Adsorbed Residual Chlorine at Adlineation Sites over Formation of Pt/HxMoO₃

Jin Gul Kim* and Seong-Soo Kim**

활성점에 흡착된 잔존 chlorine이 Pt/HxMoO₃ 생성에 미치는 영향

김진걸* · 김성수**

Abstract Kinetics of H-spillover over Pt/MoO₃ was greatly affected by the amount of residual chlorine differing by calcination temperature. Multifacetted techniques for characterization were dedicated to elucidate the faster reduction of chlorine in the isothermal reduction (ITR) at 50°C after calcination. Reduction of residual chlorine over platinum resulted in opening the more channel of hydrogen pathway into more MoO₃ particles and controlling the kinetics of hydrogen uptake.

요 약 Pt/MoO₃로의 수소 이동 속도론은 소성 온도에 따라 변하는 잔존 Cl량에 의하여 영향을 받았다. 선택적 CO 화학흡착 법을 사용하여 소성 온도의 증가에 다른 Pt 표면적의 감소를 측정하였다. 50℃ 등온 실험에서 소성 후에 Cl 량의 빠른 감소 현상을 규명하기 위하여 여러 특성화 분석을 실시하였다. Pt 결정 표면에서 잔존 Cl 량의 감소는 MoO₃로의 수소 공급을 증가시켰고, 수소 흡착 속도론을 조절하였다.

Key Words: H-spillover, Pt/MoO₃, Calcination, H₂ uptake, residual chlorine

1. Introduction

Calcination of Pt/MoO_3 increased the rate of H_2 uptake from Pt to support MoO_3 resulting in hydrogen molybdenum bronze (H_xMoO_3) [1,2]. The concept of hydrogen spillover was applied to explain the kinetics of H_2 uptake over Pt/MoO_3 . It is well documentated that the rate determining step in bronze formation is the actual spillover step [3], in which atomic H migrates from the Pt surface to the trioxide lattice.

Molecules adsorbed at the metal-trioxide interface have been documented to increase the rate of this H_2 spillover step [1]. It was reported that water molecule present at addineation sites between Pt and MoO_3 increased to uptake H_2 into Pt/MoO_3 .

Residual chlorine was also considered to be one of possible factors to affect H.spillover from Pt to

MoO₃. Chemisorption study over Ru/SiO₂ showed that the amount of residual Cl greatly influenced the chemisorptive capacity of Ru for CO, O₂ and especially H₂ which adsorbs dissociatively on Ru [4]. Reduction study of PtCl_x over SiO₂ increased the temperature at which reduction of PtCl_x in H₂ starts from 140°C and finished at 190°C [5]. According to these notions, it is expected that reduction at 50°C of PtCl_x precursor impregnated onto MoO₃ might not serve to eliminate all chlorine.

2. Experimental Procedure

Ammonium heptamolybdate (AHM, Aldrich Co., USA) was dried in an oven at 500°C overnight. The AHM was completely changed to an orthorhombic crystalline MoO₃ [6]. An appropriate weight of H₂PtCl₆.6H₂O (Aldrich Co., USA) was dissolved in an amount of deionized water sufficient to ensure the complete wetting of the support. The concentration of the metal precursors in the solution used for

Division of Material and Chemical Eng., Soonchunhyang Univ., Asan 337-745, Korea

Clean Energy Research Dept., Korea Institute of Energy Research, Yusongku, Daejon

impregnation was adjusted to give a nominal metal loading of 1 wt% Pt for supported MoO₃ catalysts. The slurry became Pt/MoO₃ after drying in an oven open to air at 100°C overnight and then ground into a fine powder. The reactor was run in the recirculation mode with a nominal flow rate of 30 sccm and a recycle ratio of 70. The thermocouple inside catalyst bed measures the temperature of gas stream. A mixture of 2% H₂ in N₂ was used for reduction experiment at 50°C and the progress of reduction was monitored using a thermal conductivity detector. After purging reactor with He, a pulse chemisorption by CO was continued to measure free Pt surface area.

In situ XPS spectrometer (SSX 100, Amoco Co. USA) was employed to analyze the chemical state of the surface of calcined Pt/MoO₃ in reduced condition. Reduction has been performed in 30 ml/min of H₂ for 15 min at 50°C during pretreatment.

3. Result and Discussion

To explain the effect of Pt precursor on hydrogen spillover over Pt/MoO₃, kinetics of hydrogen spillover as shown in Fig. 1 and 2 have been performed under the condition of isothermal temperature at 50°C and




Fig. 1. Effect of calcination on H_2 uptake at an elevated high temperature




Fig. 2. Effect of an elevated calcination temperature on morphology of Pt/MoO₃ (a) Ratio of H/MoO₃ (b) free Pt surface area (unit: mmole) (c) Pt crystallite size (unit: mm)

at atmospheric pressure, after Pt/MoO₃ was pretreated in an oven as a function of an elevated calcination temperature.

With a MoO₃ sample only, no H₂ uptake occurs since MoO₃ cannot activate to uptake hydrogen at 50°C without presence of Pt [3,7]. CO does not adsorb since there is no active site available. The noncalcined Pt containing MoO₃ exhibits a relatively slow initial reduction rate and has a slow long tail. For noncalcined and 100°C calcined samples, the initial sinuous curves of H₂ uptake in 15 minutes indicate the very significant "auto-accelerative" behavior [8,9]. Calcination at 200°C temperatures increases the initial reduction rate, and decreases the size of the spectral tail. With 200°C calcined Pt/MoO₃, the amount of specific CO uptake is approximately constant or increases slightly while the ITR spectra show the increased initial reduction rate.

As shown in Fig. 1, it was found that the rate of H-uptake increased as the temperature of calcination of the Pt/MoO₃ samples was increased. Two factors might be considered for an account for the reason of these trends; physisorbed water or water formed during the reduction and residual clorine on Pt.

The presence of water has been reported to increase the H₂ spillover rates [10]. Rate of hydrogen spillover at 50°C is expedited by the presence of water on the adlineation sites [1]. It might be considered that even with feeding the completely dry hydrogen gas, hydration of surface of Pt/MoO₃ produces a small amount of water, which acts as a carrier.

However, in this Fig. 3, water was not seemed to play a role to control H-spillover as shown in Fig. 1, because there were large differences in H₂ uptake kinetics by changing calcination temperature. Therefore, this possibility can be eliminated because this




Fig. 3. Effect of water on H₂ uptake over Pt/MoO₃




Fig. 4. Effect of residual chlorine on H_2 uptake

would have affected all the experiments if it did. Gravimetric measurements and differential thermal analysis by Sermon and Bond [3] have shown that lower oxide formation does not occur below 200°C. [3] The volumetric measurements of water released during the bronze formation and NMR study results by Fripiat showed again that there was no noticeable formation of a hydrated lower oxide such as Mo₂O₅.H₂O below 200°C [11]. According to this notion, it was accepted that water would not be formed under the reduction condition of this set of experiments at 50°C. Thus, it is believed that water formation does not affect the H₂ uptake kinetics.

The effect of residual chlorine on H-spillover was investigated with partially physical mixtures of MoO₃ and different Pt chloride precursors. ITR pattern at 50°C of these samples are shown in Fig. 4.

As the ratio of Cl/Pt decreased, initial rate of H_2 uptake increased and amount of H_2 uptake became higher. This indicated that the chlorine played the dominant role to control the kinetics if H-spillover over Pt/MoO₃.

Effect of residual chlorine on H-spillover is now discussed via Cl/Pt ratio and electronic state of Pt crystallite. XPS result as shown in Fig. 5 and Fig. 6 has been dedicated to investigate chemical composition of PtCl_x precursor over surface of Pt crystallites.

Effect of reduction on the change of Cl/Pt ratio as shown in Fig. 5 has appeared to be very drastic for the 200°C calcined Pt/MoO₃ compared to noncalcined Pt/MoO₃. Cl/Pt ratio has changed from 4.1/1 to 4.7/1 for the noncalcined Pt/MoO₃, which is not significant. In contast to this, this number has dropped to almost to trace levels for 200°C calcined Pt/MoO₃. Reduction of Cl/Pt ratio in the XPS experiment is expected




Fig. 5. Cl/Pt ratio of Pt/MoO₃




Fig. 6. XPS result for an electronic state of Pt as a function of calcination temperature

to be similar to the trend from the results of ITR experiment. This results indicated that Cl play a role to dominate the H-spillover rates from Pt to surface of MoO₃.

Electronic state of Pt crystallite as shown in Fig. 6 has been in the state of Pt⁺² for all Pt/MoO₃ samples before reduction. After reduction, 43% of Pt has changed into metallic Pt⁰ for noncalcined Pt/MoO₃, while 75% of Pt has changed into metallic Pt⁰ for 200°C calcined Pt/MoO₃. This results indicated that Cl play a role to dominate the H-spillover rates from Pt to surface of MoO₃.

4. Concusion

Calcination results in faster hydrogen uptake, even if dispersion of Pt crystallites did not change. Amount of residual chlorine analyzed by characteristic techniques of XPS and CO chemisorption reduced more faster in ITR at 50°C after calcination at higher temperature. This lessoning of residual chlorine resulted in opening the more channel of hydrogen pathway into more MoO₃ particles and controlling the kinetics of hydrogen uptake.

Acknowledgment

The collaboration of Dr. Kim and the technical support from Korea Research Council of Public Science and Technology is greatly acknowledged for the completion of this work.

References

- P. A. Sermon and G. C. Bond, J. Chem. Soc. Faraday I., 72, 730, 1976.
- [2] J. J. Fripiat and D. Tinet, J. De Chimie Phy. et de Phy. Chim. Bio., 76, 867, 1979.

- [3] G. M. Pajonk, Appl. Catal. A, 202, 157, 2000.
- [4] T. Narita, H. Miura, K. Sugiyama, T. Matsuda, and R. D. Gonzalez, J. Catal. 103, 492, 1987.
- [5] B. Rejai and R. D. Gonzalez, J. Catal. 123, 113, 1990.
- [6] X. Lin, J. Francois, H. Lanmbert, and J. J. Fripiat, J. Catal. Lett., 3, 169, 1989.
- [7] G. C. Bond and J. B. P. Tripathi, J. Less Common Metal, 36, 31, 1974.
- [8] J. J. Fripiat, R. Erre, and H. Van Damme, Surf. Sci. 54, 365, 1983.
- [9] J. J. Fripiat, R. Erre, and M. H. Legacy, Surf. Sci. 127, 69, 1983.
- [10] J. E. Benson, H. W. Kohn, and M. Boudart, J. Catal. 5, 307, 1966.
- [11] G. M. Pajonk, Appl. Catal. A, 202, 157, 2000.