Development of Web-based Design Review System for Reliability and Safety Knowledge Management

Yuichi Otsuka*, Takashi Yukawa¹ and Yoshiharu Mutoh²

Top Runner Incubation Center for Academy-Industry Fusion, Nagaoka University of Technology, 1603-1 Kamitomioka, Nagaoka, Niigata 940-2188, Japan

¹Department of Electrical Engineering, Nagaoka University of Technology, Japan

²Department of System Safety, Nagaoka University of Technology, Japan

(Received May 17, 2010; Accepted November 25, 2010)

Abstract: This paper describes a web-based design review system as a knowledge management system relating reliability and safety system design. Since people's consciousness for safety and security become sensitive and increases the need of establishing a proactive prevention method for internal failures and relating risks in products. It also means that prevailing tacit knowledge in retired workers, in order to transform them to be easily used to support new system development, become more important. When considering safety and reliability design, at least two data sheet are necessary; Failure Modes and Effects Analyses (FMEA) and Risk Assessment (RA). These two data are practically made separately. However, it includes the concerns that a risk by failures during long-term use may not be noticed. To overcome this insufficiency, a support tool for integrating reliability evaluation and risk assessment data simultaneously is expected to be revealed. The authors have then developed a web-based design review system for reliability and safety system design. The system include various profitable functions; making FMEA and RA sheet, retrieving past data sheet for engineering change management and new product development and web-based discussion to increase the efficiency of discussion. The system is applied to one practical development works in order to demonstrate its effectiveness that is to be made clear by interviewing user's qualitative comment.

Key words: design review, FMEA, risk management, knowledge management

1. Introduction

In Japan, consciousness of people for safety and security has recently become sensitive. In a product development stage, checking the safety of a product in advance is then required. When it comes to consider reliability and safety design, Failure Modes and Effects Analysis (FMEA) [1]) and Risk Assessment (RA) [2]) are normally used to identify latent hazards in products and evaluate their degrees of risks for customers. In long time use of products, a concern of risk that a fracture of structure harms users may increase, e.g., a broken cable in an electric circuit causes fire by electric shorts. According to ISO code for RA, a hazard of fracture during service is listed. However, it does not contain the way of predicting a specified content of the

fracture that is necessary to consider its countermeasure. On the other hand, FMEA data sheet contains Fault Tree Analysis (FTA) to link a failure mode between its causes but not includes a hazard list to discuss effect of the failure mode for users. To support for predicting these hazards by failure modes, it is necessary to make FMEA and RA sheet at the same time with ease.

Conventional data for reliability or safety assessment is stored by papers. This preservation system is easier to be operated. However, it also has difficulty in searching specific data from plenty of papers by human efforts. To overcome this problem, a web-based system is suitable. Huang investigated the Hong Kong industrial company for its situation of using engineering change management system [3-4]. Though ISO guideline of engineering change management has already published, the company only introduced paper based system using their original forms, which has difficulty in searching a

^{*}Corresponding author: otsuka@vos.nagaokaut.ac.jp

specific related document to concern potential errors in a current change. Huang also developed a web-based design review system [5-7] to discuss effects engineering changes, which is helpful to preserving the detailed contents of the reviews. Peng and Trappey [8] proposed a data model of a product compatible to ISO. Bouikni also developed a design review system based on the concept of Product Features Evolution Validation Model (PFEV) [9] to discuss the effect of changes in design stage. However, they discussed little in defining engineering changes and in finding errors involved in the changes through a design review process. These systems scopes for normal design reviews, which includes concept design, functional design or component design etc. However, these systems did not consider the process of detecting failures in their design concepts and connections of results of reviews to a specific form of data sheet for FMEA or RA. Furthermore, little discussions have been conducted to predict latent failures in current design concepts by using past data effectively.

One of the authors proposed the Design Review Based on Failure Mode (DRBFM) to predict latent failures by focusing the engineering changes or environmental changes that was visualized by comparisons design features with past reliable one [10-11]. This method is applicable for the complex products which has hierarchical structures [11]. The DRBFM method can be helpful in detecting much amounts of failures more than the one taken by using conventional FMEA [12]. This kind of design reviews can also be useful in On-the-job training by means of transporting know-how from veterans to younger workers [13]. Combining the DRBFM method and ISO based RA is useful and necessary to simultaneously discuss the reliability and safety of products designing. The stored data will be helpful in discussing the failures in next products. The web-based design review system based on the DRBFM and RA is then necessary in order to manage the framework of design reviews in workplaces.

This paper describes a framework of web based design review system as a knowledge management system relating reliability and safety system design. The developed system is applied in development case of one pressure vessel system for food processing. The effectiveness of the system is investigated.

2. Web-based Design Review System

2.1 Role of participants

A design review system normally needs the following




Fig. 1. Entire structure of design review system.

participants in order to fulfill a FMEA or a RA data sheet.

• Manager

A person who decides participants in design review, monitors a process of making data sheets and manages a schedule of review.

• Designer

A person who makes a DRBFM and a RA sheet for a composite of his /her charge.

• Reviewer

A person who checks whether enough causes of failure modes and risks are predicted based on his / her profession.

Adviser

A person who checks whether all of failure modes or risks are treated by appropriate solutions and the contents of solutions are fulfilled explicitly in data sheets

2.2 Structure of the design review system

Fig. 1 Entire structure of design review system shows an entire structure of a developed web-based design review system. The system is composed of the following functions.

Inputting data sheet

A designer can make data sheets for engineering change management, reference codes, standards, Design Review Based on Failure Modes (DRBFM) [13] sheets and Risk Assessment (RA) sheets.

• Web-based review

A reviewer and an adviser can check input data sheet using web-browser and give a designer comments for a revision or a recommendation.

• Referring past data

All participants can search past data in order to check past identifications for failure modes or risks and their




Fig. 2. Work flow of making DRBFM and RA data sheets in one proto-type design model.

管理者	, phys	(P)	A	6
大塚その2	ð		8	a
大塚雄市	6	•		۱
大導器者		0	0	•
Sho Takiguchi	#	. 6	â	40

Fig. 3. Example of selecting roles of participants.

measures.

Knowledge data base

This design review system can stock four data sheets; engineering change management data, codes and standards, DRBFM sheets and RA sheet. This function will help manager to monitor a process of discussion and analyze contents of these sheets.

2.3 Flow chart of design review

Fig. 5 shows a flow chart of design review in making one proto-type design model.

1. Registering roles

Manager decides participating designer, reviewer and adviser from a registered list (Fig. 2). When all the participants are determined, a case that is an unit data set including four data sheets and explanations for a model is made (Fig. 4).

2. Determining changes from a past design model

Fig. 5 Example of engineering change management; comparing differences in design features of a current model from a previous one

Fig. 2 Work flow of making DRBFM and RA data sheets in one proto-type design model



Fig. 4. Example of one registered case.

***	728 07 0775		ロヴィンユーザー(大幅器
品の練習条件の変更			
#K-warr		BOARD TO THE WAY BY A PERSON NOW AND ADDRESS OF THE PERSON NAMED IN COLUMN 2 I	SMM or
16/P:		the full communities of the forest party. Hold	VENT THEF
Mga reserri		a record Landminster death of the	的作品表现:我们是出现了这一少年不是不是老人的前于了。
	72 / 4	Sec. 10. 10. 10. 10. 10. 10. 10. 10. 10. 10	MARKET STATES OF THE STATES
w.e	3G.4 2w-3	45.4 ps - 25.4 2 (4.5 (4.5 (4.5 (4.5 (4.5 (4.5 (4.5 (4.5	がたシフェースをサストランス・ボー(株)。
	92015 x 2002	Par - Barrets ag. >	SE-SBONG &
	90, 4 St. 28 - 100 8 4 5	5-(19),85	分下數學。 西海河海岸沿
	N 6	13.3.4	F. 1975 *
	RC-85-74	29.92.424	組織でいるも
	5.4 × 6. 8	A(では30米ードの名間時からなる)	14.67.14.2.28.14.18.14.18.66.
	59~3	2.F-2001L-5.6	スセータを使用した。64.1
	20/24	これが14年間、むか	1274年100年。11.00年
	#3 K35K, OLEMS 1	※ボベンルフラブサー・他等略、たいない	世主でアルンDマクトので **後期。**X/4。
	36.Fx-9	FKG #840915	(2)(4)(大)(4)(4)(4)
	#24K/S4C001-	77 COSC 51 100 Rt 10 C	53-24/6-3 20 -34-5-4

Fig. 5. Example of engineering change management; comparing differences in design features of a current model from a previous one.

At first, a designer makes a list of engineering changes in his design from previous one and also checks an environmental change in service condition. Fig. 5 is an example of comparing list of engineering changes in design features. A designer can predict failure modes in a current model with ease by using the comparing list because differences shown in the list mean new points on a past reliable design condition that may cause a new failure mode. The list helps a designer to focus on the differences in his complex model to identify reliability problems. If a service environment has also changed, its content should also be listed, as shown in Fig. 5 Example of engineering change management; comparing differences in design features of a current model from a previous one. Because there are so many accident reports caused by not considering an environmental change, e.g., temperature, roughness of road etc.

3. Inputting data sheets

A designer subsequently makes a DRBFM work sheet and a RA work sheet. Fig. 6 illustrates an example of a DRBFM work sheet. In normal, these sheets are made by paper or an office soft. However, such kind of data form has difficulty in searching contents of failure modes in order to use a past data in checking whether sufficient failure modes can be predicted in a current

事例		マスタ保守	ログアウ	ንት					ログ	インユー	ゲー:大塚	推市(アドバイザ,管理	
温の故障・	影響評価(DR	BFMシート作品	()									者	1
MID: testi				製品相	前型: http://sdfrs.ne	zaokautac	io/ikms/d	rewines/ima001-200	90613220047pdf				
例名称:						***************************************	- Albany	rownes/ime001 200					
Mark test1						94011001100	2						
							:2-7il(n)	thich seemed and the	北田野水原 たしる山の	開発性はごか	17月春会	わせると表示されます	r.
- 過 額対	影形 位	90	l à	聖氏模造	R.W.E			基の対応	OA THE SECOND			デガイン レ	
8/8/8	杨素	故障モード	一機織	9 (4)	伊用無人の影響	華華寮	区分	対応内容	例れるの対象内容	*6.W	柳田		
アロントフェンダー k(ま		泥がかかる	容応力誘導	器引機応力の過少		9	対征海	許容引殊応力の計	許容引導応力の計算し なおし				
プロナフェンダー 販売ギルト	プロントフォークと プロントフェンダー の締結	ボルトが切れて機 結できない	衝撃箭重による許 容応力超過	衝撃荷重による許 音せん断応力の達 少	使用額難 (けがをする恐れなし)	8	対応海	衝撃消滅による許容せん断応力の計 質しなおし	衝撃荷重による終容せ ん断応力の計算しなお し				-
		療労による強度係 下	使いすぎによる病 命の超過	使用延騰(けがをす う恐れなし)	В	27E)\$	機労試験を行い使用可能期間を明示 する	腰骨試験を行う					
			の超過	過少	使用困難 (けがきす る恐れなし)	В	対応済	許容線め付け力の 計算しなおし	許容権的付け力の計算 しなお。				
	ホルトが優んで確 結できない		みの蓄積	使用困難 (けかをす ら恐れあり)	A	対応導	険しパンテナンス の期間を明示する	ボルトの緩みの試験を 行う					
			微動摩耗	使いすぎによる緩 みの蓄積	使用圧難 (けがきする恐れあり)	A	封応済	験しメンテナンス の期間を明示する	ポ月十の組みの試験を (行)				
			衝撃による反発	(先) けざによる緩 みの番積	使用医難(けがをする恐れあり)	A	対応済		ポルトの緩みの試験を 行う				
ゴムツイヤ本は 解覚を吸収、接他 大 する	穴が閉いて衝撃が 吸収できない		OMT	使用困難 (けがをする恐れあり)	A	封応署	製造業が興命にどのX.EL 影響を及 はずか試験をし、使 用可能期間を明示 する	試験をする					
			摩託による強度低 下	(外) すぎによる美命	使用困難 (けがをす る恐れあけ)	A	河北海	寿命試験をし使用 可能期間を明示す る	興命経験を行う				-
				固定ボルトが様む ・ハブが傾く(カー ブ走行時)		A	対応済	プロントフェンダー 国定ボルトが検ま ないようカバーきす さ				プロ・トフェンダ - 固定 ポルトが確まない ようカ パーをする	
			組いものが刺さっ た	悪路での走行	使用制難(けがをする恐れあり)	A	316.3		圧縮試験を行い許容圧 縮原力を明示する・タ イヤを厚くする			- Contambours	
				製造工場に訊いる のが散らばってい た	使用胚腫(けがをする恐れ遊り)	A	村店海	作業環境の見直し				作業理境の見直し	
		潜が游って接触し にくくなる	摩耗による砂度低 下	使いすぎによる事 命	使用困難 (けがをす る恐れあり)	A	対応済	趣命試験をL使用 可能基礎を明示する	舞命計験を行う				
ガ本体	スポークとの締結	破損して回転運動 が伝わられる	衝撃荷重による許 交に力軽機	衝撃荷重による許 改を提出されの過少	使用不可	S	対応済	病禁剤動による許	衝撃前重による許容引 選択力が計算しなおし	<u> </u>	 		

Fig. 6. Example of Design Review Based on Failure Modes work sheets.

品の複雑条件の重要			
esp:		\$64 dill to stronger at 2 min man cold 1988.	
MECHANIA MECHANIA		http://debraspines.educa/tyre/tything/pedit/, 200000	LSAL Yare
		Amount of the damks of	网络美术小科人民 主义公司 - 小女子会会中主人最大发生。
H-A-D	The state of the s		Total Section 1
(2 P	73.12597	ALA 34-3541 C74 BAD 14443 C1	537577577
	XX.4-3	メルカフェ・フェマン たりも 水を高さ てを得せ合い力 な	X1,434 - 2139,13134,18-480;
	100 miles (100 miles (\$500 m 17 \$6 (30) \$6, max.	THE CONTRACTOR
	など・フィンタ・開発をより	247 m (B)	20世帯には、世帯には高級な
	7. *	No.70 · 4	F x 2 77% 4
	5	Shani viet	#E 7 1.5%
	₹-{- <u>%</u> #	3×ビュンスター2が金額を計った。4	December 1985
	34-4	(18 - 19 (18) (18)	17年・2年後期、日本会・
	196	1. x 16. 医糖糖工作 在	Corpulation Control
	# 8 T.C. W. 25 9 25 W T A	47-7-4 - Paris (1884)	#11-12 ★ 25/26/17 (政策 , 15/4)
	EL4	्रव अ वश्र ा	1.7. St. 4.28 A. G.
	2 2 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	が100mmの15mmの13	ETHER STREET

Fig. 7. Example of engineering change management; comparing differences in service environment.

design. By using data base management system, such problem can easily be solved.

4. Data check by a reviewer

A reviewer can check all of the contents in data sheets by using a web-browser. If he wants to give a message to a designer, a communicating board is useful to send a comment and stock a process of discussion, as shown in Fig. 9.

5. Data check by an adviser

An adviser also checks the contents of data sheets, especially in contents of solutions for predicted failure modes or risks. Because error might also be involved in a contents of the solutions and it's difficult in finding them without enough profession on product's behavior.



Fig. 8. Example of design review board on web-browser.

6. Evaluating quality of data sheets

A manager can evaluate a quality of data sheets in views of finding errors, causes and enough solutions. These evaluating data can indicate a good data sheet for




Fig. 9. Example of searching box. Only cases in process are shown in a search result. A manager can monitor a schedule of making data tables.

next users.

2.4 Management functions

A manager can search each case by using a searching table, as shown in Fig. 6. By using this monitor function, a manager can easily see which cases are finished on schedule. If he notices a delayed case, he contacts an adviser of the case whether a help is needed. The manager also arranges contents of items in each column of data sheet by using sheet masters.

If a next design stage starts, a new case, which succeeds to all contents in a previous type model, can be updated. This function helps managers to store a history of design changes through a development stage.

3. Case Studey: Risk Assessment of Pressure Vesses System

3.1 Target of the application

The target of the case study is a pressure vessel system for food-processing. Figure 11 shows the specification of the prototype model of the pressure vessel system. This vessel system can operate suppresses inner water at the maximum pressure of 200 MPa. Inserted food-packs are then pressured. Complex structures of proteins in the foods are changed during pressurizing. The high pressure process can reduce the hardness of meats that can improve their taste and can also reduce the allergen in the foods, which is expected to make less-allergy foods for patients.

However, the vessels are subjected to such the high pressure, designers should be sensitive for the structural reliability and related risk of the vessel. Once the walls of the vessels were broken in operating, the flying pieces of the broken walls will be critical hazard for surrounding users. We applied DRBFM and RA for the vessel system with the help of the developed web-based design review system.



Fig. 10. Example of a master table. A manager can easily change a name of each item.




Fig. 11. Entire structure of the pressure vessel system for food processing. The cover is moved down by hydraulic forces and fixed by arm guides in pressurizing.

3.2 Result of DRBFM

Fig. 12 shows the result of DRBFM for the pressure vessel system shown in Fig. 11. Original data was stored according to the form shown in Fig. 6 and was written in Japanese. We then translated it to English form in order to demonstrate the specific result clearly. Ranks in the figure mean the extents of possible damage for both the function of the considering parts and the users. The failure modes of higher ranks involve serious hazards for the users. In this case, cracks on the wall of vessels or arms can have the hazards of abnormally high pressure or breaking the wall. Table 1 shows the result of risk assessment. We could predict 23 risk scenarios from the failure modes shown in Figure 12.

The data shown in Fig. 12 and Table 1 is beneficial

Parts	Function	Function Failure Mode			
Pressure vessel	The pressure vessel endures inner pressure	A crack penetrates through thickness. → Impossible to keep internal pressure.	S		
Water Compressor main body		A crack penetrates through thickness in the cylinder. → Impossible to send the water.			
main body increases the pressure of the pressure container.	An increase in pressure by false operation. —Cylinder break down—Increasing pressure abnormaly by misuse.	SS			
Gland		Thickness decreases. →Impossible to prevent the water leak.			
	The gland sticks fast with the cylinder and prevents the water leak	A crack penetrates through thickness. →Impossible to prevent the water leak.	В		
		The gland harden and the space open. →Impossible to prevent the water leak.	В		
Pressure meter	The pressure meter make	The pressure meter break down. → Impossible to confirm the pressure.			
	person confirm the pressure in the pressure tube.	The pressure meter jounce. → Impossible to confirm the pressure.	С		

Fig. 12. A part of DRBFM work sheets for the pressure vessel system. Original data was stored in the form shown in figure 6 and was translated to English.

Table 1. Number of total failure modes and related risk scenarios for the pressure vessel system

	Failure modes (Partly shown in Fig.12)	Related Risk Scenarios (Using hazards in ISO 14120)		
Number of predictions	53	23		

for the designers in making the countermeasures for the risks related to failure modes. Designers should give failure modes a specific rank that is the basis of determining the needs of countermeasures for them. However, ranking was highly based on the designers past experiences that is not easy for discuss its rationality. In the case of RA, designers also consider countermeasures for higher risks. They may have difficulties in the consideration that the cause of risks is unknown when the target of risks related to failure modes. The data is stored in DRBFM data sheets, not in RA sheets. By combining both the method, the designers can decide rational ranking for failure modes with specific evidence of risks using RA data and also determine profound measures for the causes of failure modes, which can also reduce the extent of risks inherently.

In this process, the adviser and the designer of the DRBFM and RA work sheet had only a few meeting for discussions in order to check the process of using the system and the quality of final data sheet. During

the process, the adviser ordered the designed to change or revise the contents using the design review board shown in Fig. 8. The system can help the workloads of the design review process, which will be effective in improving the quality and cost-competiveness of the reliability and safety design by reducing the cost of management processes.

4. Summary

This paper introduced a web-based design review system for reliability and safety design for a product, which can contain both FMEA and RA data sheets. A designer can identify a risk in using a product with looking a result of FMEA, which is expected to focus on predicting hazards by failures. Furthermore, these failure modes are recorded in risk assessment sheet. The developed system will improve a quality of design review by decreasing a managing load (making data sheets, stocking them in a regulated form and making a meeting time for discussion frequently) and by preventing participants from overlooking possible failure modes or hazards.

Acknowledgments

A part of this work is financially supported by the research project of Japan Science and Technology Agency (JST). The authors would sincerely thank Prof. Takabumi FUKUDA and Associate Prof. Yukio

MIYASHITA of Nagaoka Unversity of Technology for their critical comments and advises. We also acknowledge Syo TAKIGUCHI for his helps in the analyses of the case study.

References

- [1] M.G. Stewart and R.E. Melchers, *Probabilistic Risk Assessment of Engineering Systems*, Chapman & Hall, London, 1992.
- [2] ISO12100-1, 2003.
- [3] GQ. Huang and K.L. Mak, "Computer aids for engineering change control", *Journal of Materials Processing Technology*, vol. 76, no.1-3, p. 187-191, 1988.
- [4] G.Q. Huang, W.Y. Yee and K.L. Mak, "Current practice of engineering change management in Hong Kong manufacturing industries", *Journal of Materials Processing Technology*, vol. 139, no. 1-3 SPEC) p. 481-487, 2003.
- [5] GQ. Huang, W.Y. Yee and K.L. Mak, "Development of a web-based system for engineering change management", *Robotics and Computer-Integrated Manufacturing*, vol. 17, no. 3, p. 255-267, 2001.
- [6] G.Q. Huang, "Web-based support for collaborative product design review", *Computers in Industry*, vol. 48, no. 1, p. 71-88, 2002.
- [7] G.Q. Huang, J.B. Zhao and Z. Jiang, "Web-based design review portal with fuzzy set theoretic methods for fuel pump designs", *International Journal of Computer Integrated Manufacturing*, vol. 17, no.3, p.

- 265-278, 2004.
- [8] T. Peng, and A.J.C. Trappey, "A step toward STEP-compatible engineering data management: The data models of product structure and engineering changes', *Robotics and Computer-Integrated Manufacturing*, vol. 14, no. 2 p. 89-109, 1998.
- [9] N. Bouikni, A. Desrochers and L. Rivest, "A product feature evolution validation model for engineering change management", *Journal of Computing and Information Science in Engineering*, vo. 16, no. 2, p. 188-195, 2006.
- [10] H. Shimizu and T. Yoshimura, "Reliability Problem Prevention Method of Stimulating Creativity and Visualizing Problems 1st report", *Trans. Japan Soc. Mech. Eng. Series C*, vol. 70, no. 689, p. 243-250, 2003.
- [11] H. Shimizu, Y. Otsuka and H. Noguchi," Design review based on failure mode to visualize reliability problems in the development stage of mechanical products", *Int. J. Vehicle Design*, vol. 53, no. 3, p. 149-165, 2010.
- [12] Y. Otsuka, et. al., "Empirical consideration for the effectiveness in checking the error of under estimating in conducting failure analyses", Proc. of ASME International Mechanical Engineering Congress and Exposition, in submitting, 2010.
- [13] Y. Otsuka, H. Shimizu and H. Noguchi, "Efficacious design review process including on-the job training in finding misunderstand errors", *International Journal of Reliability, Quality and Safety Engineering*, vol. 16 no. 3, p. 281-302, 2009.